

## Chains

68.30 Saddle on ridge, 25 ft. below ascent, bears N.10°W. and S.15°W. Ascend.

73.27 Intersect N. bdy. of Tp. 1.48 chs. N.89°39'W. from the former cor. of secs. 3 and 4, and now an angle point only, as restored by me. At intersection,  
Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground for the closing cor. of secs. 3 and 4, marked on brass cap:

T33N R49E

T32N

1916

and raise a mound of stone 2 ft. base, 1½ ft. high, S. of cor.

Land, rolling hills.

Soil, clay and gravelly loam and rocky, with a hard clay subsoil.

Undergrowth sagebrush and greasewoods.

Very little grass for grazing.

No timber.

Note: The corners set by Mr. W. A. Pray, U.S. Surveyor, between the following sections were removed, and with the exception of the stone corners, which I destroyed, his iron posts were re-marked and used:

Secs. 1 and 2, 2 and 3, 3 and 4, 2 and 11, 3 and 10, 4 and 9, 11 and 12, 10 and 11, 9 and 10, 11 and 14, 10 and 15, 9 and 16, 14 and 15, 15 and 16, 16 and 17, 15 and 22, 16 and 21, 22 and 23, 21 and 22, 20 and 21, 21 and 28.

From the reestablished cor. of secs. 4 and 5 on the N. bdy. of the Tp., S.10°0'W. on a random retracement line (by calculation) bet. secs. 4 and 5.