

Retracement of S. bdy. of T.33 N., R. 49 E.

Chains.

sq. 2 ft. above the ground, marked and witnessed as described by the Surveyor General. I remove the 1 in. iron post set by Mr. Pray.

46.90 Bottom of hollow, 80 ft. below spur, course NW. Ascend.

51.60 Top of spur, 50 ft. above hollow, bears N. and S.

Descend.

52.80 Bottom of hollow (same as last crossed) 60 ft. below spur, course S. about 2 chs. then NW. Ascend.

57.50 Top of spur, 60 ft. above hollow, bears N. and S.

Descend.

59.00 Bottom of hollow, 10 ft. below spur, course NW. Ascend.

70.40 Top of spur, 140 ft. above hollow, bears NW. and SE.

Continue gentle ascent.

77.80 Top of ridge, 30 ft. above spur, bears N. 20°E. and S. 20°W. Descend gently.

80.22 The old Maxson cor. of secs. 33 and 34, which is a cedar post, 3 X 4 ins. sq. 18 ins. above the ground, and marked and witnessed as described by the Surveyor General.

I deface all the marks on the post, and remove the 3 in.

iron post and also the closing cor. of secs. 3 and 4, set by Mr. Pray

Land mountainous, rolling.

Soil, clay and gravelly loam and rocky.

Very little grass for grazing.

Undergrowth sage brush.

No timber.

The old Maxson $\frac{1}{4}$ sec. cor bet. secs. 33 and 34 is a cedar stake 2 X 3 ins. sq. 24 ins. above the ground, and marked $\frac{1}{4}$ S on W face, with plain trace of pits. I re-dig the pits as follows: Dig pits 18 X 18 X 12 ins. N. and S. of post 3 ft. dist.; and raise a mound of earth, 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Thence S. 0° 5'W. (A flag set on the cor. $\frac{1}{2}$ mile S. is