```
Chains
              Top of spur, 55 ft. above hollow, bears N.20°E.
  21.30
              Desc.
              Bottom of hollow, 130 ft. below spur, course N.20°E.
 29.50
              Top of spur, 40 ft. above hollow, bears N.20°H. and
 33.20
              S.20°W.
              No trace of the original closing cor. of secs. 1 and 2,
              Desc.
  38.34
              can be found after diligent search.
                    This point satisfies the requirements of the propor-
              tion for the proper position of this corner as out-
              lined in "Supplemental Special Instructions for the Survey
              of Corrective Work in Group 27, Nevada." dated March 8
              1916, as amended by the Commissioners letter E-WCH, dated March 30, 1916. Therefore, at this point Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in the ground, for the closing corner of secs. 1 and 2,
               with brass cap mkd:
                                                         T 31 N
                                                              $35
                                                       S34
                                                                 CC R50E
                                                              sz si
                                                                 T30N
                                                                1916
               dig pits 24x18x12 ins. crosswise on each line, E. and W. 3 ft. and S. of cor. 7 ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, S. of cor. Head of Hollow, 45 ft. below spur, course N.20°E.
   39.20
               Top of spur, 20 ft. above hollow, bears N.15°E.
   42.60
                Desc.
                Bottom of hollow, 80 ft. below spur, course N.10°E.
   50.00
               Mid point on the S. side of sec. 35.

Set an iron post 3 ft. long, l in. in dia., 26 ins. in the ground for the \( \frac{1}{4} \) sec. cor., on the S. side of Sec. 35, with brass cap mkd:
   52.26월
                                                            S35
                and raise a mound of stone 2 ft. base, l_2^1 ft. high,
                N. of cor.
                Top of spur, 60 ft. bove hollow, bears N. and S.
    58.60
               Desc.

Point 325 ft. below spur.

This point satisfies the requirements of the proportion for the proper position for the cor. of secs. 35 and 36, (angle point corner) as outlined in "Supplemental Special Instructions for the Survey of Corrective Work in Creap No.27, Nevada," dated March 8, 1916, as amended by the Commissioner's letter E-WCH, dated March 30, 1916.

No trace of the original cor. of secs. 35 and 36 can be found after diligent search: Therefore, at this point
                Desc.
    89.32
                be found after diligent search; Therefore, at this point Set an iron post 3 ft. long, 3 ins. in dia., 24 ins. in the ground for angle point, only, with brass cap mkd:
                 25-100
                                                           T31N R50E
                                                                 1916
                 and raise a mound of stone 2 ft. base, l^{\frac{1}{2}} ft. high,
                 N. of cor.
                 Land, mountainous, rolling.
Soil, gravelly and rocky, from 1 to 2 ft. deep. Subsoil
the same, but harder.
                  Undergrowth, sagebrush.
                 Good grass for grazing.
                 No timber.
```