

Retracement of W. Bdy. of T. 31 N., R. 50 E. 11.

Chains. The course of this $\frac{1}{2}$ mile is S.0°30'W., and the length 39.88 chs.

39.70 South on a retracement bet. secs. 31 and 36.
Fall 49 lks. E. of the old $\frac{1}{4}$ sec. cor. bet. secs. 31 and 36, a willow stake, 1 in. in dia., $2\frac{1}{2}$ ft. long, with only faint traces of marks, loose on an old mound with traces of pits.

Course of this $\frac{1}{2}$ mile S.0°42'W., and the length 39.70 ch.
I set up over corner and continue South.

39.65 Fall 49 lks. E. of the old S. C. of Tps. 31 N., Rs. 49 and 50 E., which is a badly decayed willow stake, with only traces of marks remaining, lying loose on an old mound with plain traces of old pits. The course of this $\frac{1}{2}$ mile is S.0°42'W., and the length 39.65 chs.

I reestablish this corner as follows:

Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground for the cor. of secs. 31 and 36, with brass cap mkd:

T31N
S36 | S31
R49E | R50E
1914

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

December 5, 1914: At 11h 50m a.m., 1. m. t., I set off 22°19' S. on th decl. arc; and observe the sun on the meridian; the resulting latitude is 40°27' N.

Thence N.0°42'E. on a resurvey bet. secs. 31 and 36. Over rolling mountainous land, through dense sagebrush, descend.

2.70 Old pony express road, bears NW. and SE.

3.45 Hollow, 20 ft. below road, drains NW., asc.

7.05 Ridge, 40 ft. above hollow, bears N.70°W. and S.70°E., desc.

10.05 Hollow, 30 ft. below ridge, drains N.80°W., asc.

13.25 Ridge, 30 ft. above hollow, bears E. and W., desc.

33.50 Swale, 40 ft. below ridge, drains W., asc.

38.35 Ridge, 20 ft. above swale, bears N.70°W. and S.70°E., desc.

39.65 The old $\frac{1}{4}$ sec. cor. already described, which I reestablish at the same point as follows:

Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for the $\frac{1}{4}$ sec. cor. for sec. 36, only, with brass cap mkd:

$\frac{1}{4}$ S36

1914

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Subsequently,

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for the $\frac{1}{4}$ sec. cor. for sec. 31, only, with brass cap mkd:

$\frac{1}{4}$ S31

1918

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

42.65 Hollow, 30 ft. below ridge, drains N.80°W., asc.

44.55 Ridge, 30 ft. above hollow, bears N.80°W. and S.80°E., desc.

50.65 Old road, bears N.20°E. and S.20°W.

79.35 The old cor. of secs. 25, 30, 31 and 36, already described. I reestablish as follows:

Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground for the cor. of secs. 25 and 36, only, with brass cap mkd: