

Chains

From the cor. of secs. 10 and 11.
Thence retracing East between secs. 11 and 14.

35.69 The $\frac{1}{4}$ sec. cor. for sec. 14.

38.82 Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for the $\frac{1}{4}$ sec. cor. for sec. 11, with brass cap mkd:

S11 $\frac{1}{4}$
1915

and raise a mound of stone 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

From the cor. of secs. 10 and 11,
Thence retracing West on south bdy. of sec. 10.

4.23 The cor. of secs. 14 and 15.

Thence S.89°54'W., on south bdy. of sec. 10.

40.785 Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for the $\frac{1}{4}$ sec. cor. for sec. 10, only, with brass cap mkd:

S 10 $\frac{1}{4}$
1915

dig pits 18x18x12 ins. E. and W. of cor. 3 ft. dist., and raise a mound of earth 3 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

May 18, 1915.

At the cor. of secs. 1, 2, 11 and 12, at 8 h 0 m, a.m. l.m.t., I set off 40°33'N. on the lat. arc; 19°25'N. on the decl. arc, and determine a meridian with the solar. Thence N.0°13'W. on a survey between secs. 1 and 2. Over level land in bend of river.

6.50 S. bank of river, bears E. and W. Thence across river, course W.

9.25 N. bank of river, bears E. and W.

Ascend steep S. slope.

21.20 Mountain ridge, bears E. and W. 275 ft. above river. Desc.

28.30 Ravine, course W. 35 ft. below ridge. Asc.

35.00 Mountain spur, slopes W. 200 ft. above ravine. Along W. slope.

40.00 Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for the $\frac{1}{4}$ sec. cor., with brass cap mkd:

S2 | S1 $\frac{1}{4}$
1915

and raise a mound of stone 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of cor.

Descend NW. slope.

53.10 Ravine, course W. 80 ft. below corner.

61.60 Ravine, course SW. 195 ft. above previous ravine. Asc.

68.40 Mountain spur, slopes W. 100 ft. above ravine. Desc.

73.10 Ravine, course W. 85 ft. below spur.

81.34 Intersect the N. Bdy. of the Tp. 3.35 chs. E. from the corner of secs. 35 and 36.

At point of intersection set an andesite stone 16x14 x10 ins. 10 ins. in the ground for the closing corner of secs. 1 and 2, marked with 1 groove on the E., 5 grooves on the W., and CC on the S. face, and raise a mound of stone 2 ft. base, 1 $\frac{1}{2}$ ft. high, S. of cor. Land, S. 9.25 chs. is level land along Humboldt River.