

Chains

stone, marked 1-3647 A., bears S.45°40'E., 5.30 chs. dist. This is Cor. No.1 of Good Hope, No.7 Lode, Survey No.3647-A.

43.00 Hollow, 50 ft. below $\frac{1}{4}$ sec. cor., course E. Asc.


52.00 Ridge, 200 ft. above hollow, bears N.20°E. and S.15°W. Desc.

61.00 Head of swale, level with ridge, course NE. Asc.

67.50 Ridge, 50 ft. above swale, bears NW. and SE. Desc.

80.84 Intersect the S. Bdy. of the Tp. at a point 66 lks. W. of the cor. of secs. 2 and 3, heretofore described.

At the point of intersection, set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in the ground for the closing corner of secs. 34 and 35, with brass cap mkd:



and raise a mound of stone 2 ft. base, 1 $\frac{1}{2}$ ft. high, N. of cor.

Land, mountainous.

Soil, stony, clay loam, 2nd rate. Subsoil the same.

No timber.

Undergrowth, dense sagebrush.

Good grass for grazing.

Drainage N. 67.50 chs. to the NE.; the S. 13.34 chs. to the SE.

Scott P. Stewart,
U.S. Surveyor.

August 22, 1914.

By Ruban W. Riley, U.S. Transittman.

Survey commenced Aug. 13, 1914, and executed with a Young & Sons transit No.8146, with Smith Solar attachment. For description and approval of instrument see Book "A" of this survey.

For adjustment of transit and tests of solar apparatus see commencement of the S. Bdy. of this survey.

August 13:

At 7 h 0 m, a.m., l.m.t., I set off 40°44' on the lat. arc; 14°51'N. on the decl. arc; and determine a meridian with the solar at the cor. of secs. 4, 5, 32 and 33, on the S.Bdy. of T. 34 N., R. 51 E., heretofore described.

Thence North on a retracement between secs. 32 and 33.

40.00 No trace of original $\frac{1}{4}$ sec. cor.


80.00 No trace of original cor. of secs. 28, 29, 32 and 33.

Thence North between secs. 28 and 29.

40.00 No trace of the original $\frac{1}{4}$ sec. cor.

82.00 Fall 99 lks. W. of an old partly decayed stake, all marks obliterated, lying in an old mound of earth, with very faint traces of pits. I regard this stake as the original cor. of secs. 20, 21, 28 and 29, and remonument the corner as follows:

Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in the ground for the cor. of secs. 20, 21, 28 and 29, with brass cap mkd:



dig pits 18x18x12 ins. in each section 5 $\frac{1}{2}$ ft. dist., and