

Resurvey of the S. Bdy. of T. 33 N., R. 52 E.

1.

Chains

Surveyed by Scott P. Stewart.
 Survey commenced Aug. 1, 1914.
 For description, approval, adjustment of the transit and tests of solar apparatus see commencement of the subdivisions of this Tp.
 I begin at the tp. cor. of Ts. 32 and 33 N., Rs. 51 and 52 E., which is a quartzite stone, 8x12x24 ins., marked with 6 notches on four sides, R 52 E., on the E. face, T 33 N., on the N. face, lying in a stone mound I remonument the corner as follows:
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground for the cor. of Ts. 32 and 33 N., Rs. 51 and 52 E. with a brass cap mkd.,

T 33 N	
R 51 E	R 52 E
S 36	S 31
S 1	S 6
T 32 N	
1914	

and raise a mound of stone, 2 ft. base, 1½ ft. high S. of corner.

Thence I run

E. on a retracement bet. secs. 6 and 31.

40.87 Fall 34 lks. N. of the old ¼ sec. cor. which is a cedar stake 3 ins. square, 3 ft. long, loose on top of ground, marked ¼ S. No other marks visible.

80.96 Fall 68 lks. N. of the cor. of secs. 5, 6, 31 and 32 heretofore described in commencement of the subdivisions of this township by R.W. Riley.

Thence I run

N. 89° 31' W. on a true line of resurvey bet. secs. 31 and 6.

Over rolling land.

Descend on S.W. slope through dense sage brush.

3.50 Head of hollow, course S.E., 30 ft. below sec. cor., ascend.

6.70 Ridge, 40 ft. above hollow, bears N. and S. 20° W., descend.

11.60 Hollow, 40 ft. below ridge, course N.W., ascend.

12.60 Spur, 12 ft. above hollow, projects N. 30° W., descend.

13.10 Hollow, 5 ft. below spur, course N., ascend.

17.70 Ridge, 20 ft. above hollow, bears N. and S., descend.

36.10 Hollow, 40 ft. below ridge, course N. 25° E., ascend.

40.09 The original ¼ cor. above described. I reset same and also set an iron post 3 ft. long, 1 in. dia., 26 ins. in the ground for ¼ cor. with brass cap mkd.,

S 31

¼

S 6

1914

Dig pits 18x18x12 ins., E. and W. of cor. 3 ft. dist. and raise a mound of earth, 3½ ft. base and 1½ ft. high N. of cor.

40.10 Ridge, 20 ft. above hollow, bears N. 30° E. and S. 30° W., descend.

55.60 E. side of wash, 30 ft. below ridge, bears N. 20° E.

56.60 Road, bears N. 30° E. and S. 30° W.

57.40 Wash, 20 lks. wide, 3 ft. deep, course N., ascend along S. side of hollow.

80.96 The tp. corner of Ts. 32 and 33 N., Rs. 51 and 52 E., heretofore described.

Land rolling.

Soil; rocky and gravelly clay loam, 2nd and 3rd. rate, subsoil same. No timber.

Undergrowth; dense sagebrush, good grass for grazing.

Drainage; S. W. in general.

Scott P. Stewart,

U. S. Surveyor.

Aug. 1, 1914