

Resurvey of N. Boundary T. 33 N., R. 52 East.

Chains

and raise a mound of stone, 2 ft. base; 1½ ft. high E. of corner.

Ruban W. Riley,
U. S. Transitman

Aug. 8, 1914.

Surveyed by Scott P. Stewart.

Aug. 8: I begin at the ¼ cor. of sec. 1 heretofore described.

Thence I run

S. 0° 4' W. bet. secs. 1 and 6.

4.61

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for the ¼ cor. of sec. 6, with brass cap mkd.,

| ¼ S 6
1914

and raise a mound of stone, 2 ft. base, 1½ ft. high E. of corner.

Scott P. Stewart,
U. S. Surveyor,

Aug. 8, 1914.

RESURVEY OF THE N. BDY. OF T. 33 N., R. 52 EAST

Surveyed by Scott P. Stewart.

Aug. 8: At the tp. cor. of T. 33 and 34 N., R. 51 and 52 E., heretofore described, At 12h. 6m., p.m., l.m.t., I set off 16° 14' N., on the decl. arc; and observe the sun on the meridian, the resulting latitude is 40° 44'.

Thence I run

E. on the N. bdy. of sec. 6 on a retracement.

40.80

Fall 3 lks. S. of the original ¼ cor. of secs. 6 and 31 which is a cedar stake 3 ins. in dia. and 3 ft. above ground marked ¼ S., no other marks visible, I remonument corner as follows:

Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for the ¼ cor. of secs. 6 and 31 with a brass cap mkd.,

S6
| ¼
S31
1914

and raise a mound of stone, 2 ft. base, 1½ ft. high N. of corner.

Thence I run E. from this ¼ sec. cor.

80.89

Fall 4 lks. S. of the cor. of secs. 5, 6, 31 and 32 hereinafter described.

Thence I run

S. 89° 57' W. on a true line bet. secs. 6 and 31. Over rolling mountainous land.

Ascend gently through sage brush.

40.09

The ¼ sec. cor. of secs. 6 and 31, heretofore described.

57.60

Ridge, 240 ft. above sec. cor., bears N. 80° E. and S. 85° W. descend.

64.85

Bottom of saddle, 20 ft. below ridge, ascend.

78.40

Head of draw, 40 ft. above saddle, bears N. 40° E., ascend.

80.89

The tp. cor. of T. 33 and 34 N., R. 51 and 52 E., heretofore described.

Land; rolling mountains.

Soil; stony clay loam, 3rd. rate, subsoil same.