

18.

Retracement of South Bdy. sec. 31, T. 31 N., R. 52 E.

Chains

From the Standard S.W. Cor. of T. 31 N., R. 52 E.,
I retrace
East on the south bdy. of sec. 31.
12.56 The Closing Corner of T. 30 N., R. 51 and 52 E.,
previously described.

RESURVEY OF SOUTH BDY. Sec. 31, T. 31 N., R. 52 E.

From the Closing Corner of T. 30 N., Rgs. 51 and 52 E.,
I resurvey
West on the south bdy. of sec. 31.
Ascend east slope of low ridge.
12.56 The Standard S.W. Cor. of T. 31 N., R. 52 E. I repair
the accessories but do not change the corner.

RESURVEY OF EAST BDY. Sec. 36, T. 31 N., R. 51 E.

From the Standard S.W. Cor. of T. 31 N., R. 52 E.,
I resurvey
S. 0° 11' W. on the east bdy. of sec. 36, T. 31 N., R. 51 E.
Ascend N.E. slope of ridge.
3.96 Ridge, bears NW. and SE. Descend steep slope to ravine.
8.22 Small spur, slopes SW. 50 ft. below ridge. Continue
to descend.
11.78 Small spur, slopes SW. 215 ft. below previous spur.
Continue to descend.
13.96 Draw, course SE. 90 ft. below spur.
15.95 Spur, slopes SE. 15 ft. below draw. Descend.
21.53 Deep ravine, course E. 130 ft. below spur. Ascend.
23.55 Spur, slopes NE., 80 ft. above ravine. Descend.
25.62 Draw, course NE. 55 ft. below spur. Ascend steep slope.
31.21 The $\frac{1}{2}$ sec. cor. on the east bdy. of sec. 36. I repair
the accessories but do not change the corner.
42.85 Top of steep slope, bears E. and W. 355 ft. above draw.
Ascend gradually.
61.69 Top of flat ridge, bears E. and W. 50 ft. above top
of steep slope.
Descend steep slope toward ravine.
71.02 250 ft. below top of slope.
The Standard S.E. Cor. of T. 31 N., R. 51 E.
Land mountainous, on east slope of Cortez mountains.
High ridges and deep ravines, with steep side slopes.
Soil; very dry, rather thin and shallow, gravelly loam,
much washed on the slopes, unfit for cultivation, 3rd
rate.
Good growth sagebrush, fair grass, scattering juniper
timber on the north 20.00 chs. Good grazing land.
August 2, 1915.

RESURVEY OF 6th STD. PAR. N., through R. 51 E.

August 3, 1915.

I destroy all trace of the old standard corner of
secs. 32 and 33, and reestablish it at the same point
as follows:

Set an iron post 3 ft. long, 3 ins. in dia., 24 ins.
in the ground for the Standard cor. of secs. 32 and 33,
with brass cap mkd:

T 31 N	
R 51 E	
S32 S33	
S C	
1915	

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.