

## 26. Resurvey of Fract. Subdivision in T.30 N., R. 51 E.

Chains

S17	S16½
1915	

and raise a mound of stone 2 ft. base, 1½ ft. high,  
W. of cor.

Descend N.W. slope.

63.30 Ravine, course W. At foot of mountains, bear NE. and SW.  
270 ft. below corner. Descend gradually over slope  
at foot of mountains.

77.74 Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in  
the ground for the cor. of secs. 8, 9, 16 and 17, with  
brass cap mkd:

T 30 N	
R 51 E	
S8	S9
S17	S16
1915	

dig pits 18x18x12 ins. in each sec. 5½ ft. dist.,  
and raise a mound of earth 4 ft. base, 2 ft. high,  
W. of cor.

Land, S. 63.30 chs. is steep rough, volcanic mountains  
with a slope to the N.W. The north 14.44 chs. is  
land at the foot of mountains, sloping to the N.W.

Soil; dry, coarse texture, gravelly and rocky. Shallow  
3rd and 4th rate, unfit for cultivation.

Fair growth of sagebrush, some grass and weeds, no timber.  
Fair grazing land.

August 12, 1915.

August 13, 1915.

I begin at the Closing Corner of Secs. 3 and 4, on the  
North Bdy. of the township, on the 6th Standard Parallel  
North.

This corner is a volcanic stone firmly set in the  
ground of the size, marked and witnessed as described by  
the Surveyor General. I destroy all trace of this corner  
and its accessories and reestablish it at the same point  
as follows:

Set an iron post 3 ft. long, 2 ins. in dia., 24 ins.  
in the ground for the Closing Corner of secs. 3 and 4,  
with brass cap mkd:

T 31 N	
R 51 E	
S33	S34
C	C
S4	S3
T 30 N	
R 51 E	
1915	

and raise a mound of stone 2 ft. base, 1½ ft. high,  
S. of cor.

At 8 h 0 m a.m., l.m.t., I set off 40°29'N. on the  
lat. arc, 14°54'N. on the decl. arc, and determine  
a meridian with the solar.

Thence I resurvey

S.0°23'E. between secs. 3 and 4.

Over rolling land, sloping to the N.W.

11.90 Road, bears E. and W.

13.60 Wash, course W.

14.50 Road, bears NW. and SE.

Begin ascent of North slope.

23.20 Wire fence, bears E. and W.

26.60 Spur of hill, slopes E., 135 ft. above wash.

Descend SE. slope.

36.20 Road, bears NE. and SW. 60 ft. below spur.

36.40 Wire fence, bears NE. and SW.

38.15 Wire fence, bears E. and W.

39.60 Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in  
the ground for the ¼ sec. cor., with brass cap mkd:

S4	S3½
1915	