

## 8. Resurvey of Frac. Subdivision in T.29 N., R.52 E.

Chains

79.67 Thence N.0°3'W.  
The cor. of secs. 9, 10, 15 and 16.  
I destroy all trace of this old cor. and its accessories and reestablish it at the same point as follows:  
Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in the ground for the cor. of secs. 9, 10, 15 and 16, with brass cap mkd:

T29N	
R52E	
S9	S10
S16	S15
1915	

dig pits 18x18x12 ins. in each sec. 5½ ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, W. of cor.

40.00 N.0°06'W. between secs. 9 and 10.  
The old ¼ sec. cor.  
I destroy all trace of this old corner and its accessories and reestablish it at the same point as follows:  
Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for the ¼ sec. cor., with brass cap mkd:

S9	¼ S10
1915	

dig pits 18x18x12 ins. N. and S. of cor. 3 ft. dist., and raise a mound of earth 3½ ft. base, 1½ ft. high, W. of cor.

79.98 Thence N.0°14'W.  
The cor. of secs. 3, 4, 9 and 10.  
I destroy all trace of this cor. and its accessories and reestablish it at the same point as follows:  
Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in the ground for the cor. of secs. 3, 4, 9 and 10, with brass cap mkd:

T29N	
R52E	
S4	S3
S9	S10
1915	

and raise a mound of stone 2 ft. base, 1½ ft. high, W. of cor.

40.00 North between secs. 3 and 4.  
Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for the ¼ sec. cor., with brass cap mkd:

S4	¼ S3
1915	

dig pits 18x18x12 ins. N. and S. of cor. 3 ft. dist., and raise a mound of earth 3½ ft. base, 1½ ft. high, W. of cor.

80.00 The cor. of secs. 3, 4, 33 and 34.  
I destroy all trace of this corner and its accessories and reestablish it at the same point as follows:  
Set an iron post 3 ft. long, 3 ins. in dia., 24 ins. in the ground for the cor. of secs. 3, 4, 33 and 34, with brass cap mkd:

T30N	
R52E	
S33	S34
S4	S3
T29N	
1915	