

Chains

dig pits 18x18x12 ins. in each sec. 5 1/2 ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, W. of cor.


39.80

S.89°06'W. between secs. 5 and 32. The old 1/4 sec. cor. I destroy all trace of this corner and its accessories and reestablish it at the same point as follows: Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for the 1/4 sec. cor., with brass cap mkd:



80.56


dig pits 18x18x12 ins. E. and W. of cor. 3 ft. dist., and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high, N. of cor. Thence S.89°44'W. The old cor. of secs. 5, 6, 31 and 32. I destroy all trace of this corner and its accessories and reestablish it at the same point as follows: Set an iron post 3 ft. long, 3 ins. in dia., 24 ins. in the ground for the cor. of secs. 5, 6, 31 and 32, with brass cap mkd:



dig pits 18x18x12 ins. in each sec. 5 1/2 ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, W. of cor.

39.76


S.89°33'W. between secs. 6 and 31. Set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for the 1/4 sec. cor., with brass cap mkd:



dig pits 18x18x12 ins. E. and W. of cor. 3 ft. dist., and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high, N. of cor.

77.10

Cor. of Tps. 29 and 30 N., Rgs. 51 and 52 E. I destroy all trace of this cor. and its accessories and reestablish it at the same point as follows: Set an iron post 3 ft. long, 3 ins. in dia., 24 ins. in the ground for the cor. of Tps. 29 and 30 N., Rgs. 51 and 52 E., with brass cap mkd:



dig pits 24x24x12 ins. on each line N., E. and W. 4 ft. and S. of cor. 8 ft. dist., and raise a mound of earth 5 1/2 ft. base, 2 1/2 ft. high, S. of cor.

July 20, 1915.