

2.

Resurvey of the 7th Standard Parallel North,
South of Sec. 31, T. 36 N., R. 57 E.

Chains

the ground on an old mound of earth;; markings obliterated by weathering.

Difference between two measurements of 80.66 chs. measured twice by the same set of chainmen is 6 lks., position of middle point

By 1st measurement 80.63 chs.,

By 2nd measurement 80.69 chs., the mean of which is

80.66 The standard cor. of secs. 31 and 32, on line.

A willow stake 2 ins. diam. by 18 ins. long, lying on the ground on an old mound of earth; the markings have been obliterated by weathering.

From the Standard Cor. of T.36 N., Rgs. 56 and 57 E.,
I resurvey

East on the 7th Standard Parallel North, south of sec.31,
T.36 N., R. 57 E.

I continue to measure the distances twice with the same set of chainmen and to take the mean of their measurements.

Difference between two measurements of 40.33 chs. measured twice with the same set of chainmen is 8 lks., position of middle point

By 1st measurement 40.29 chs.

By 2nd measurement 40.37 chs., the mean of which is

40.33 The old standard $\frac{1}{4}$ sec. cor.

At this point set an iron post 3 ft. long, 1 in. in dia., 24 ins. in the ground for the standard $\frac{1}{4}$ sec. cor., with brass cap mkd:

S 31 $\frac{1}{4}$
SC

1915

dig pits 18x18x12 ins. E. and W. of cor. 3 ft. dist., and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N. of cor.

79.28 The old closing cor. of secs. 5 and 6, T. 35 N., R. 57 E.

At this point set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in the ground for the closing corner of secs. 5 and 6, with brass cap mkd:

T36N	R57E
S 31	

C C	
S6 S5	
T35N	R57E
1915	

dig pits 24x24x12 ins. in each section 6 ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, S. of cor.

Difference between two measurements of 80.66 chs. measured twice with the same set of chainmen is 6 lks., position of middle point

By 1st measurement 80.63 chs.,

By 2nd measurement 80.69 chs., the mean of which is

80.66 The old standard cor. of secs. 31 and 32.

At this point set an iron post 3 ft. long, 3 ins. in dia., 24 ins. in the ground for the standard cor. of secs. 31 and 32, with brass cap mkd:

T36N	R57E
S31	S32
S C	

1915	

dig pits 24x24x12 ins. crosswise on each line E. and W. 3 ft. and N. of post 7 ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high, N. of cor.

stop