

Retracements of Subdivisions in Camp Halleck U. S. Military Reservation.

Chains

14.33 Fall 2.97 chs. S. of the old $\frac{1}{4}$ sec. cor., which is a granite stone, 6x14x4 ins. above the ground, firmly set, mkd. and witnessed as described by the surveyor general. The bearing of this line is therefore S. $78^{\circ}18'$ E., and the length 14.63 chs. From this cor., I retrace West bet. secs. 19 and 30. 20.70 Fall 20 lks. S. of the old closing cor. of secs. 19 and 30, on W. bdy. of reservation, previously described. The bearing of this line is therefore S. $89^{\circ}26'$ E., and the length 20.70 chs.

Dependent Resurvey of N. Bdy. T. 33 N., R. 59 E.

As there are subdivisions depending upon every part of this bdy., I preserve the old alignment of the entire bdy. As there are however no subdivisions to the south from the E. Bdy. of the Tp. westward to the E. Bdy. of the reservation, I set new corners referring to the south side of the line, at intervals of 40.00 and 80.00 chs. Longitudinally from the E. Bdy. of the Tp. Also reestablish corners proportional on the N. side of the line, where they are obliterated and reconstruct others.

At the true point for closing cor. of Tps. 33 and 34 N., R. 59 E. previously described.

Set an iron post, 3 ft. long, 3 ins. dia., 24 ins. in the ground, for closing cor. of Tps. 33 and 34 N., R. 59 E., with brass cap mkd.

T34N
R59E
S36
CC S1
T33N
R59E
1917

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Thence N. $86^{\circ}41'$ W. on N. Bdy.