

34

Dependent Resurvey of W. Bdy. T. 33 N., R. 59 E.

Chains to the east, except in sec. 6, I set new corners referring to T. 33 N., R. 59 E., at intervals of 40.00 and 80.00 chs., beginning at the reestablished cor. of Tps. 32 and 33 N., R. 59 E., previously described in Book of T. 32 N., R. 59 E.

Thence

North, 16.90 chs. to cor. of T. 32 N., R. 58 E., previously described in Book of T. 32 N., R. 58 E.

Thence

S.89°58'E, 8.61 chs. to the old cor. of Tps. 32 and 33 N., Rs. 58 and 59 E., previously described, in Book of T. 32 N., R. 58 E. I change this cor. to a cor. of T. 33 N., R.

58 E. as follows:

Set a granite stone, 18x16x8 ins., 12 ins. in the ground, for SE. cor. of Tp. 33 N., R. 58 E., mkd. with 6 notches on N. and W. edges; from which

An aspen, 5 ins. dia., bears N. 48° 45' E., 17 lks. dist., mkd. T. 33 N R 59 E S31 B T.

An aspen, 5 ins. dia., bears N. 34° 30' W., 24 lks. dist., mkd. T 33 N R 58 E S 36 B T.

Thence on a resurvey on W. Bdy. of township. N. 0° 17' E., on E. Bdy. of sec. 36., T. 33 N., R. 58 E.

Over rough mountainous land, through, asc. SW. slope, through heavy dense timber and heavy dense undergrowth.

3.50 Leave heavy dense timber, bears NW. and SE.

23.10 Set an iron post, 3 ft. long, 1 in. dia., 18 ins. in the ground to bed rock, and 6 ins. in a mound of stone, for $\frac{1}{4}$ cor. of sec. 31, with brass cap mkd.

 $\frac{1}{4}$

S31

1917

and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, E. of cor.

27.50 Top of ridge, 280 ft. above Tp. cor., bears N. 60° W., and S. 60° E.; desc.

39.21 The old $\frac{1}{4}$ sec. cor.; I change this cor. to $\frac{1}{4}$ cor. of sec. 36, as follows:

Set a granite stone, 15x14x4 ins., 10 ins. in the ground,