

Chains

the ground for the $\frac{1}{4}$ sec. cor., with brass cap mkd:

$$\begin{array}{r} \frac{1}{4} S 20 \\ \frac{1}{4} S 29 \\ \hline 1915 \end{array}$$

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Corner is set 110 ft. above creek.

- 43.20 Top of spur, 15 ft. above $\frac{1}{4}$ sec. cor., projects SE.
- 48.20 Little draw, 5 ft. below spur, course SE.
- 52.25 Top of spur, 90 ft. above draw, projects S.10°E.
- 57.20 Draw, 55 ft. below spur, course S.
- 62.20 Spur, 25 ft. above draw, projects S.
- 67.10 Draw, 45 ft. below spur, course S.
- 75.25 Very rocky ridge, 85 ft. above draw, bears SW. and NE.
- 80.00 Set an iron post 3 ft. long, 2 ins. in dia., 15 ins. in the ground to solid rock and in a mound of stone, for the cor. of secs. 19, 20, 29 and 30, with brass cap mkd:

T34N	R61E
S19	S20
S30	S29
1915	

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, W. of cor. Corner is set 50 ft. below ridge.

Land mountainous.

East half of mile, yellow clay mixed with some sand and coarse gravel. Very stony; quartzite stones; no outcrops. Soil about 20 ins. deep on stones and coarse gravel. At $\frac{1}{4}$ sec. cor., solid granite outcrops about 5 chs. to NW. Spring at 43 chs. and to west, solid granite outcrops and huge boulders, with decomposed granite gravel, and a little sandy loam. From ridge at 75.25 chain point to section corner is solid rock and slide rock of quartzite.

No timber. Undergrowth, sage, service berry, choke cherry and buck brush. A very little grass.

West between secs. 19 and 30.

Over rolling foot hills.

- 27.65 Bottom of draw, 515 ft. below section corner, course SW.
- 32.60 Top of spur, 20 ft. above draw, projects SW.
- 40.00 Set an iron post 3 ft. long, 1 in. in dia., 26 ins. in the ground for the $\frac{1}{4}$ sec. cor., with brass cap mkd:

$$\begin{array}{r} \frac{1}{4} S 19 \\ \frac{1}{4} S 30 \\ \hline 1915 \end{array}$$

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. Corner is set 10 ft. below spur.

- 79.03 Intersect the W. Bdy. of the Tp., 95 ft. below $\frac{1}{4}$ sec. cor., at a point 2.10 chs. S.0°56' E. of the cor. of secs. 24 and 25, T. 34 N., R. 60 E., heretofore described.

At point of intersection, I set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in the ground and in a mound of stone for the closing corner of secs. 19 and 30, with brass cap mkd:

T 34 N	
R60E	R61E
S25	S19C
	S30C
1915	

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, E. of cor.

Land rolling.

East 7.00 chs. is solid rock and slide rock. Thence gradually less rocky. At $\frac{1}{4}$ sec. cor. and remainder of mile is cold, heavy, yellow clay soil with a little gravel; all very stony; quartzite boulders.