

Resurvey of subdivisions, T. 29 N., R. 40 E.

Chains

Undergrowth, sage and desert brush, bunch grass.

No timber.

The bearing and distance bet. the cor. of secs. 25, 26, 35, and 36, and the $\frac{1}{4}$ cor. of secs. 35 and 36, having been found by previous retracement, therefore I run,
S. 00° 1' E. on a true line bet. secs. 35 and 36.

Over east slope valley land descend 20 ft.

9.80 Dry wash, 25 lks. wide, course east, ascend gradually 17 ft. to the $\frac{1}{4}$ sec. cor.

40.11 The old $\frac{1}{4}$ cor. of secs. 35 and 36, heretofore described. I reestablish the cor. at the center of the mound of earth as follows;

Set an iron post 3 ft. long, 1 in. diam., 16 ins. in the ground to bed rock and in a mound of stone, for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, with brass cap mkd.;

$$S35 \frac{1}{4} \quad | \quad S36$$

$$1914 \quad ;$$

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high. W. of cor.

I now change bearing and run,

South on a random line. bot

Over valley land sloping east gradually descend 43 ft. to the township boundary.

6.65 Wagon road, bears S. 45° E. and N45° W.

39.95 The old cor. of secs. 1, 2, 35 and 36, which is a post 3-3 ins. by $2\frac{1}{2}$ ft. long, firmly set in a mound of earth, mkd. and witnessed as described by the surveyor general, bears W. 6 lks. dist. I reestablish a new cor. alongside the post as follows;

Set an iron post 3 ft. long, 3 ins. diam., 24 ins. in the ground for the cor. of secs. 1, 2, 35, and 36, Tps. 28 and 29 N., R. 40 E., with brass cap mkd.;