

Resurvey of the subdivisions T. 29 N., R. 40 E.

Chains retracement north along same line and at 39.99 chs. intersect E. and W. line, 41 lks. E. of the old cor. of secs. 11, 12, 13, and 14, which is a quartzite stone 4-6-10 ins. above ground, firmly set, mkd. and witnessed as described by the surveyor general. The total distance from the cor. of secs. 23, 24, 25, and 26 is 160.12 chs. and the bearing is N.00° 9' W.

From the cor. of secs. 11, 12, 13, and 14, I retrace N. bet. secs. 11 and 12. and at 40.00 chs. set. a temp. point for the $\frac{1}{4}$ cor. of secs. 11 and 12, no traces of the old cor. being found after careful search. I continue my retracement north along same line and at 79.96 intersect E. and W. line 21 lks. east of the old cor. of secs. 1, 2, 11, and 12, which is a willow post $2\frac{1}{2} \times 2\frac{1}{2} \times 36$ ins. long, firmly set in a mound of stone, mkd. and witnessed as described by the surveyor general. The total length of this mile is 79.96 chs. and the course is N, 00° 9' W. From the cor. of secs. 1, 2, 11, and 12, I retrace north bet. secs. 1 and 2. and at 40.00 chs. set a temp. point for the $\frac{1}{4}$ cor. of secs. 1 and 2, no traces of the old $\frac{1}{4}$ cor. being found after careful search I continue my retracement north and at 79.78 chs. intersect the north boundary of the township 7 lks. east of the old cor. of secs. 1, 2, 35, and 36, Tps. 29 and 30 N., R. 40 E, which is a granite stone 5 - 8 - 12 ins. above ground, mkd. and witnessed as described by the surveyor general. I reestablish the cor. at the same point as follows; Set an iron post 3 ft long, 3 ins. diam., 24 ins. in the ground for the cor. of secs. 1 and 2, T. 29 N., R. 40E. with brass cap mkd.;

T30NR40E

| | |
|-------|-------|
| S2 | S1 |
| T 29N | R40 E |
| 1914 | |

and raise a mound of stone 2 ft. base, $1\frac{1}{2}$ ft. high, S.

The bearing of this mile is N. 00° 3' W.

Aug. 14, 1914.