

Resurvey of portion of 6th. Standard Parallel through R. 40 E. N.

Chains

T31NR40E

S35	S36
-----	-----

1914 ;

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.

Land, mountainous and rolling valley.

Soil, rocky and stony loam, with numerous washed boulders.

Undergrowth, sage and desert brush, some grass.

No timber.

Mountainous land, 17.25 chs.

East on a true line on the south boundary of sec. 36

Over valley land sloping east, gradually descend 246 ft.

to the $\frac{1}{4}$ sec. cor.

24.55 Cross dry wash, 20 lks. wide. 10 ins. deep, in canyon, 5 chs.
wide, 20 ft. deep, course S. 60° E.

40.00 The old standard $\frac{1}{4}$ sec. cor. of sec. 36, heretofore described. I destroy all traces of the old cor. and reestablish it at the same point as follows:

Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for the standard $\frac{1}{4}$ cor. of sec. 36, with brass cap mkd.;

S36
 $\frac{1}{4}$

1914;

and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high,
N. of cor.

Descend 161 ft. to the standard Tp. cor.

44.40 Cross dry wash, 6 lks. wide, 6 ins. deep, course S. 50° E.

60.15 Dry wash, 4 lks. wide, 12 ins. deep, course S. 75° E.

62.90 Wagon road, bears S. 45° E. and N. 45° W.

64.75 The closing cor. of secs. 1 and 6, T. 30 N., R. 40 E.
previously described.

80.08 The standard cor. of T. 31 N., Rs. 40 and 41 E, heretofore