

Subdivisions of T. 30 N. R. 40 E.

Chains

80.04 The cor. of secs. 2, 3, 10 and 11.
 Land, rolling valley, draining southeast.
 Soil, light shallow rocky clay loam, rocky subsoil.
 Undergrowth, sagebrush and bunch grass.
 No timber.

N. 00° 3' E. bet. secs. 2 and 3.


Over rolling foothills, descend.

27.10 Enter willows and wild rose brush, and cottonwoods.

27.60 Creek, running water, 2 lks. wide, 2 ins. deep, 515 ft.
 below sec. cor., course S. 50° E.; ascend,

28.10 Leave willows and rose brush,, ascend mountains.

40.00 Set an iron post 3 ft. long, 1 in. diam., 24 ins. in the
 ground for the $\frac{1}{4}$ cor. of secs. 2 and 3, with brass cap
 mkd.:



and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high,
 W. of cor.

56.60 Top of ridge, 825 ft. above creek, bears E. and W.; descend.

68.30 Creek, 1 lk. wide, 2 ins. deep, 340 ft. below ridge,
 course S. 60° E.; ascend 365 ft. to the township
 boundary.

79.30 Intersect the north boundary of the township, 15.78 chs.
 west of the standard cor. of secs. 34 and 35, of T. 31
 N., R. 40 E. At the point of intersection I build a
 cor. as follows:

Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the
 ground for the closing cor. of secs. 2 and 3, with brass
 cap mkd.:

