

Subdivisions of T. 30 N., R. 40 E.

Chains

cap mkd.:

$\frac{1}{4}$  S3 ✓

1914

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
E. of cor.

43.00

46.00 Ascend. 110 ft.

60.00 To top of spur, projects N.  $45^{\circ}$  E.; descend

65.60 Bottom of gulch, 70 ft. below top of spur, course S.  $45^{\circ}$  E.

A spring bears east 1.50 chs. dist.; ascend steep slide  
rock slope, 340 ft. to the township boundary.

79.65 Intersect the 6th. Standard Parallel North, 14.48 chs.

N.  $89^{\circ}54'$  W. of the standard cor. of secs. 33 and 34, of T. 31  
N., R. 40 E. At the point of intersection, I build a  
cor. as follows:

Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the  
ground for the closing cor. of secs. 3 and 4, with  
brass cap mkd.:

T31NR40E

S33 S34 ✓

C C  
S4 S3  
1914

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
S. of cor.

From the closing cor. I run S.  $00^{\circ}$   $3'$  W. along the east  
boundary of sec. 4.

40.10 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the  
ground for the  $\frac{1}{4}$  cor. of sec. 4, with brass cap mkd.:

S4  $\frac{1}{4}$  ✓

1914

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high,  
W. of cor.

Land, mountainous.

Soil, shallow light clay loam, slide rock and barren  
outcropping lime stone ledges.