Resurvey of portion of the West Boundary of T. 31 N., R. 40 E.

Chains

Retracement by H.W.Reppert:-

Oct. 3,1914: At the old ¼ cor. of secs. 31 and 36 on the west boundary of the township, which is a quartzite stone, 8 x 10 x 12 ins. firmly set in the ground, mkd. and witnessed as described by the Surveyor General, I set off 40° 30' N. on the lat. arc; 3° 46' S. on the decl. arc; and at 8h. 25m.a.m.,l.m.t., determine with the solar a meridian.

Thence I retrace

North bet. secs.31 and 36.

40.00 Set a temp. point for the cor. of secs. 25, 30, 31 and 36. After diligent search no traces or evidence of the old cor. is found. I continue my retracement north along s same line, setting temp. points at intervals of 40.00 chs. and making diligent search for the old ¼ cor. of secs. 25 and 30, the cor. of secs. 19, 24. 25 and 30, the ¼ cor. of sess, 19 and 24, the cor. of secs. 13, 18, 19 and 24, and the ¼ cor. of secs. 13 and 18. I can find no traces of these old cor. or their accessories and at 279.65 chs. dist. from the ¼ cor. of secs. 31 and 36, I intersect E. and W. line, 37 lks. west of the old cor. of secs. 7, 12, 13 and 18, which is a quartzite stone, 7 x 8 x 12 ins., mkd. and witnessed as described by the Surveyor General. I destroy all traces of the old cor. and reestablish it at the same point as follows:

Set an iron post 3 ft. long, 3 ins. diam., 24 ins. in the ground for the cor. of secs. 12 and 13, with brass cap mkd.;

T31N

R39E	R40E
S12	
S13	

1914

dig pits, 18 x 18 x 12 ins. in each sec. 5½ ft. dist.; and raise a mound of earth, 3½ ft. base, 1½ ft. high, W. of cor.

Oct. 3, 1914.