

Survey of portion of the North Boundary of T. 31 N., R. 40 E

Chains

Surveyed by H.W.Reppert:-

Oct. 6, 1914: At 8h. 14m.a.m., l.m.t., I set off 40° 35' N. on the lat. arc; 4° 56' S. on the decl. arc; and determine a meridian with the solar at the cor. of secs. 3, 4, 33 and 34. on the north boundary of the township, already described.


Thence I run

East on a random line along the north boundary of the township, setting temp. 1/4 sec. and sec. cors. at intervals of 40.00 chs.; and at 239.95 chs. I intersect N. and S. line, 1.19 chs. N. of the cor. of Tps. 31 and 32 N., Rs. 40 and 41 E., heretofore described. The falling answers to a correction of 0° 17', or 39 2/3 lks. S. per mile, counting from the cor. of secs. 3, 4, 33 and 34.; therefore I run

N. 89° 43' W. on a true line bet. secs. 1 and 36 Over mountainous land, ascend over rocky ledges of lime-rock.

34.95 Top of spur, 650 ft. above Tp. cor., bears S. 75° E. and N. 75° W.; descend 30 ft. to the 1/4 sec. cor.

40.00 Set an iron post 3 ft. long, 1 in. diam., 6 ins. in the ground to solid rock and in a mound of stone, for the 1/4 cor. of secs. 1 and 36, with brass cap mkd.:



S1


1914

and raise a mound of stone 2 ft. base, 1 1/2 ft. high N. of cor. Descend 65 ft.

46.00 Base of descent, ascend along south slope 245 ft. to the sec. cor.

80.00 Set an iron post 3 ft. long, 3 ins. diam., 8 ins. in the ground to solid rock and in a mound of stone, for the cor. of secs. 1, 2, 35 and 36, with brass cap mkd.:

T32NR40E



S2 S1 T31N NR1914