Retracement of the 4th standard parallel N. through R. 44 E.

Chains.	
	From the ¼ sec. cor. of sec. 35, I run
	East, on the S. side of sec. 35.
34.22	Fall 4 lk. N. of the closing cor. of secs. 1 and 2, which is a limestone 8 x 10 x 16 ins., mkd. CC on S. face, 5 notches on W. and 1 notch on E., with a mound of stone 4 ft. base, 2 ft. high, S. of cor.
39.98	Fall 5 lks. N. of the standard cor. of secs. 35 and 36, which is a lime stone 8 x 8 x 12 ins. mkd. 5 notches on the west, 1 notch on the east, and SC on N. face, with mound of stone 4 ft. base, 2 ft. high, west of cor.
	The course of this line is S. 89° 56' E. and the dist. is 39.98 chs.

From the standard cor. of secs. 35 and 36 heretofore described I run

East, retracing on the S. side of sec. 36.

40.07	Fall 7 lks. N. of the old ¼ sec. cor. of sec. 36, which is a limestone 4 x 8 x 10 ins. mkd. ¼ on N. face, with a mound of stone 3½ ft. base, 1½ ft. high, N. of cor.
	The course of this line is S. 89° 54' E., and the dist. is 40.07 chs.

From the ¼ sec. cor. of sec. 36, I run

East, retracing on the S. side of sec. 36.

33.80	Fall 1 lks. N. of the closing cor. of T. 20 N. Rs. 44 and 45 E., which is a limestone 8 x 10 x 20 ins. mkd. CC 20 N. on east, 44 E. on west, 45 E. on east, and 6 grooves on the E., S. and W. faces, with mound of stone 4 ft. base, 2 ft. high S. of cor.
40.03	Fall 5 lks. S. of the standard cor. of T. 21 N. Rs. 44 and 45 E., which is a limestone 8 x 8 x 12 ins., mkd. SC on N. face, and 6 notches on N., E. and W. edges, with mound of stone 5 ft. base, 2 ft. high, N. of cor.
	The course of this line is N. 89° 56' E., and the dist. is 40.03 chs.

At 11h 44m a.m. l.m.t. I set off 16° 47' S. on the decl.