

12. Resurvey of S. Bdy. T. 39 N., R. 23 E.

Chains	S 32 <u> 1/4 </u> 1914
	and raise a mound of stone 2 ft. base, 1½ ft. high N. of corner.
63.00	Top of high mountain, bears N. 20°E. and S. 20°W.; descend 135 ft. on W. slope to new corner.
78.74	The old cor. of secs. 31 and 32, which I find to be a basalt stone, 5x9x4 ins. above ground, firmly set, marked with 5 grooves on E. and 1 groove on W. face, with mound of stone, 25 ins. base, 20 ins. high W. of corner, and which I change to an angle point by destroying the mound, effacing the markings on the stone and marking the stone AP on N face. At this point my course changes to N. 89° 42'W.
80.00	Set an iron post, 3 ft. long, 3 ins. in diam., 24 ins. in the ground, for cor. of secs. 31 and 32, with brass cap marked
	T 39 N R 23 E <u> S 31 S 32 </u> T 38 N 1914
	and raise a mound of stone, 2 ft. base, 1½ ft. high N. of corner.
	This mile is partly on the top of a high mountain and partly on its E. and W. sides. The soil is stony and rocky and unfit for cultivation. There is a sparse growth of sagebrush. No timber.
	N. 89° 42'W. on S. bdy. of sec. 31.
	Over mountainous land. Descend 145 ft. on W. slope to draw.
4.06	The C. C. of secs. 4 and 5 bears N., 1.44 chs. distant, the same being a basalt stone, 10x13x5 ins. above a mound of stone, firmly set, marked CC on S face with 4 notches on E. edge, with a mound of stone 30 ins. base, 22 ins. high S. of cor.
13.15	Draw, course NW; thence along N. slope.
19.65	Spur, projects N. 20°W. descend 710 ft. on SW. slope to second draw.
38.53	The old ¼ sec. cor., which I find to be a basalt stone, 5x8x5 ins., above ground, firmly set, marked ¼ on N. face, with a scattering mound of stone, probably originally about 24 ins. base, 18 ins. high, N. of cor, and which I change to an angle point by destroying the mound, effacing the mark on the stone and marking AP on its N. face. At this point my course changes to N. 89° 45'W.
40.00	Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for ¼ sec. cor., referring to sec. 31, with brass cap marked
	S 31 <u> 1/4 </u> 1914
	and raise a mound of stone 2 ft. base, 1½ ft. high N. of corner.
88.05	Draw, course N. 30°W.
91.75	Draw, course N.; ascend 30 ft. on E. slope to top of ridge.
95.53	The CC of secs. 5 and 6, bears N. 29 lks. dist. same being a granite stone, 13x9x4½ ins., standing in a small depression in the ground and marked CC on S., with 5 grooves on E. and 1 groove on W. face, with a mound of stone, 25 in. base, 16 ins. high S. of cor.
98.95	Ridge, bears N. and S.; descend 150 ft. on SW. slope to bottom of gorge.