		Subdivision of T. 39 N., R. 23 E. 47
14)	Ola e di a e	General Hermania (Company)
	Chains	and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high N. of
	45.00	cor. Foot of descent; ascend 25 ft. on NE. slope to top of spur.
	49.00 68.50	Spur, projects NW.; descend 230 ft. on NW. slope to draw. Draw, course N.; ascend 80 ft. on NE. slope to top of
	80.00	ridge. Ridge, bears N. and S.; descend 260 ft. on NW. slope to ravine.
	91.70	Ravine, course N. 15 W.; ascend 20 ft. on NE. slope to top of ridge.
	97.00	Ridge, course N. 5°W. and S. 5°E.; descend 145 ft. on NW. slope to draw.
	114.40 129.50	Draw, course N.; ascend 35 ft. on E. slope to top of ridge. Low ridge, bears N. and S.; descend 20 ft. on NW. slope to draw.
	135.00	Draw, course N.20°E.; ascend 30 ft. on NE. slope to top of ridge.
	139.60	Ridge, bears N. and S.; descend 25 ft. on NW. slope to head of draw.
	144.50	Head of draw, course N.10 W.; ascend 35 ft. on NE. slope to top of spur.
	146.20	Spur, projects N.; descend 40 ft. on NW. slope to draw. Large draw, course NE.; ascend 170 ft. on SE. slope.
	168.00 * 173.65	Top of ascent; descend 10 ft. on SW. slope to CC Intersect the E. bdy. of T. 40 N., R. 22 E. at a point
	10000	11.41 chs. North of the # sec. cor. on E. bdy. sec. 36 and at point of intersection set an iron post, 3 ft. long,
	The second	2 ins. diam., 24 ins. in the ground for CC of sec. 6 and 7, with brass cap marked
		T 40 N T 39 N
		R 22 E R 23 E S 25 S 6
		S 36 S 7
		and raise a mound of stone 2 ft. base, $l_2^{\frac{1}{2}}$ ft. high E. of corner.
		This mile is on rolling mountainous land draining to the N. The soil is gravelly and rocky, producing a fair growth
	Calent	of sagebrush and of bunchgrass., No timber.
	60.	N. 0° 2'W. on a true line, bet. secs. 5 and 6.
	2.50	Over rolling mountainous land. Descent 15 ft. on N. slope. Foot of descent; thence along E. slope.
	6.60	Draw, course SE.; ascend 120 ft, on SW. slope to top of ridge.
	29.00	Ridge, bears E. and W.; descend, 65 ft. on NE. slope to head of draw.
	40,00	Set an iron post, 3 ft. long, 1 in. diam., 17 ins. in the ground to solid rock, and in a mound of stone for ‡
	40,22	sec. cor, with brass cap marked
	.03,00	$S = \{0, \frac{1}{2}, S = 5, \dots, n\}$
	1.1, 30	
	-07,00	and raise a mound of stone, 2 ft. base, $l\frac{1}{2}$ ft. high W. of corner.
	55,•60	Head of draw, course N.55°E. ascend 45 ft. on SE. slope to top of spur.
	68.00	Spur, projects N.75°E.; descend 15 ft. on NE. slope to draw.
	76.30	Draw, course N.65°E.; ascend 10 ft. on SE. slope to top of ridge.
	08.	