

Chains.

34.50 Ridge bears N. and SW.; descend 545 ft. to ravine, starting on NE. slope.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.:

S 32

1/4

S 5

1915

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

47.00 Ridge, bears NE. and SW., slope changes to SE.

59.70 Rimrock, 30 ft. high, facing S. 80° E., bears N. 10° E. and S. 10° W.

76.75 Ravine, N. 50° E.; ascend 10 ft. on NW. slope to cor.

80.00 Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground, for secs. 4, 5, 32 and 33, with brass cap mkd.:

T 38 N | R 25 E

S 32 | S 33

S 5 | S 4

T. 37 N

1915

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.

Land, mountainous.

Soil, rocky.

Scattered low sagebrush and shadscale.

No timber.

East, bet. secs. 4 and 33.

Over mountainous land. Ascend 10 ft. on NW. slope to top of spur.

5.00 Spur, projects NE.; descend 250 ft. to canal, starting on NE. slope.

25.00 Slope changes to E.

35.40 Irrigation canal, 15 lks. wide, 2 ft. deep, course S.; thence over nearly level land.

40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for 1/4 sec. cor., with brass cap mkd.:

S 33

1/4

S 44

1915

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.

44.65 Road, bears N. 10° E. and S. 10° W.

69.76 The cor. of secs. 3, 4, 33 and 34, later changed to the cor. of secs. 33 and 34, as hereinafter recorded.

W. 40 chs. of this mile, mountainous. Remainder, gently sloping.

Soil, loam and rocky.

Low sagebrush and greasewood.

No timber. June 9, 1915.

RESURVEY of FRAC'L N. BDY., T. 37 N., R. 25 E.

June 9: I find the old cor. of secs. 3, 4, 33 and 34 to