

2. Resurvey of 2nd Standard Parallel N., through R. 27 East.

Chains	The course and distance of this half mile is N.89°45'E., 40.23 chs. From station 18 lks. S. of $\frac{1}{4}$ sec. cor., continue East. N. of my line 27 lks. dist., is the closing corner of secs. 2 and 3, T. 10 N., R. 27 E.
60.15	
80.76	Fall 36 lks. S. of the standard corner of secs. 34 and 35, which is a granite stone 28x14x8 ins. loosely set in a mound of stone, properly marked. The course and distance of this half mile is N. 89° 45' E., 40.53 chs.
40.59	East, retracing along S. bdy. of sec. 35. From cor. Fall 14 $\frac{1}{2}$ lks. S. of the standard $\frac{1}{4}$ sec. cor., which is a granite stone 10x10x10 ins. above ground, firmly set, marked, and witnessed as described by the Surveyor General. The course and distance of this half mile is N. 89°48'E. 40.59 chs.
58.77	From my station 14 $\frac{1}{2}$ lks. S. of the $\frac{1}{4}$ cor., continue East. N. of my line, 21 lks. is the closing corner of secs. 1 and 2, T. 10 N., R. 27 E.
81.42	Fall 29 lks. S. of the standard corner of secs. 35 and 36, which is a granite stone 9x9x16 ins., loosely set in mound of stone, properly marked. The course and distance of this half mile is N.89° 48'E. 40.83 chs.
40.41	East, retracing along S. bdy. of sec. 36. From cor. Fall 1 $\frac{1}{2}$ lks. S. of the standard $\frac{1}{4}$ sec. cor., which is a granite stone 8x12x12ins., loosely set in mound of stone, properly marked. The course and distance of this half mile is N.89°59'E. 40.41 chs.
57.87	From my station 1 $\frac{1}{2}$ lks. S. of the $\frac{1}{4}$ sec. cor., continue East. N. of my line, 2 lks. dist., is the closing corner of Tp. 10 N., Rs. 27 and 28 E., which is a granite stone, firmly set in mound of stone, no marks to be found on the stone.
80.97	Fall 3 lks. S. of the standard cor. of Tp., 11 N., Rs. 27 and 28 E., which is a trapstone 8x8x16 ins. firmly set in mound of stone properly marked. I reestablish cor. as follows: Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground, alongside of old stone, for standard township corner, with brass cap mkd.,
	<div style="text-align: center;"> T 11 N R27E R28E S36 S31 S C 1915 </div>
	and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high N. of cor. Course of dist. of last $\frac{1}{2}$ mile is N.89°59'E. 40.56 chs. July 13, 1915.

RESURVEY OF 2nd. STANDARD PARALLEL N. THROUGH R. 27 E.

July 17: At 8h 6m a.m., l.m.t., I set off 38°44' on the lat. arc; 21° 20' N. on the decl. arc; and determine a meridian at the reestablished standard cor. of Tp. 11 N., Rs. 27 and 28 E. Thence S. 89° 59' W. resurveying along S. bdy. of sec. 36. Over gently rolling land, sloping SW., through short