

Retracement and  
Resurvey West Boundary T. 11 N., R. 27 E.

7.

Chains July 14: At 7h 26m a.m., l.m.t., I set off  $38^{\circ} 44'$  on the lat. arc;  $21^{\circ} 48\frac{1}{2}'$  N. on the decl. arc; and determine a meridian at the standard cor. of Tp. 11 N., Rs. 26 and 27 E., heretofore described. Thence North, retracing bet. secs. 31 and 36.  
At 40.00 chs., failed to find any trace of the  $\frac{1}{4}$  cor.  
At 80.71 chs., fall 9 lks. W. of the cor. of secs. 25-30-31 and 36.  
Therefore I return to the standard tp. cor. and run N.  $0^{\circ} 4'E.$ , resurveying bet. secs. 31 and 36.  
Over level river bottom, through scattering clumps of buck brush along line; cultivated fields to E. and W. of line.  
0.10 Irrigation ditch, 4 ft. wide, 2 ft. deep, course E. for 20 lks., thence N.  
9.60 Forks of ditches, to W., to NW. and to N.  $20^{\circ} E.$ ; thence through pasture land.  
34.90 Fence, bears N.  $75^{\circ} E.$  and S.  $75^{\circ} W.$ ; leave all buck brush, bears NW. and SE.  
40.35 $\frac{1}{2}$  At proportional point for cor.  
Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor., with brass cap mkd.,

$\frac{1}{4}$   
S36 | S31  
1915

This is a  $\frac{1}{4}$  corner for section 36 only.

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high W. of cor.  
49.60 Fence, bears N.  $30^{\circ} W.$  and S.  $30^{\circ} E.$ ; thence gently ascend SW. slope.  
50.00 Road, Yerington to upper East Walker River, bears same.  
65.30 Road, bears N.  $80^{\circ} E.$  and S.  $80^{\circ} W.$ ; thence enter low hills, bears E. and NW.  
69.00 Low spur, projects W. 2 chs.  
71.50 Mouth of draw, course SW.  
76.00 Bottom of draw, course S.  $60^{\circ} W.$   
80.71 70 ft. above the  $\frac{1}{4}$  cor.  
The cor. of secs. 25, 30, 31 and 36, which is a trap stone 8x11x15 ins. loosely set in mound of stone, properly marked; knowing that this cor. will refer to secs. 25 and 36 only, I reestablish cor. as follows;  
Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground, alongside of stone, for cor. of secs. 25 and 36, with brass cap mkd.,

T 11 N  
R26E |  
S25 | R27E  
S36 |

1915

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high W. of cor.  
S.  $\frac{1}{2}$  mile, river bottom; with rich, dark, moist, sandy loam and alluvial soil; 1st rate; scattering clumps of buck brush, 10 to 15 ft. high; N.  $\frac{1}{2}$  mile, is gently rolling and hilly, sloping to the SW., with light, dry sandy and gravelly loam, with scattering rocks; 2nd rate.  
Undergrowth, short sheep brush and shadscale. No timber.

North, retracing and resurveying bet. secs. 25 and 30. Ascending over rolling mountainous land, facing nearly S. 35 ft.