	Chains	
	14.90 34.90 40.00	bdy. N.0° 5'W., on a true line bet. secs. 3 and 4. Over low hilly and rolling land, sloping N. and NW. Ravine, 5 ft. deep, course N. 35°W. Low spur, projects NW. 145 ft. below sec. cor., on gentle NE. slope. Set an iron post, 3 ft. long, 1 in. in dia., 16 ins. in the ground to underlying rock and in a mound of stone, for ½ sec. cor., with brass cap mkd.,
	r nove a	
	A Section of Market Section	. S4 S3
	10 A	1915
	B. 5	and raise a mound of stone, 2 ft. base, 1 ft. high W. of cor.
	62.40 65.85 80.97	Ravine, 10 ft. deep, course N. 80°W. Low spur, projects N. 70°W. Intersect N. bdy. of tp. 137 lks. N.89° 50°E. of cor. of secs. 33 and 34, heretofore described. At point of intersection, 155 ft. below 4 sec. cor., set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground for closing cor. of secs. 3 and 4, with brass cap mkd.,
*		Tlan Raye
		S33 S34 CC
		S4 S3
	· ·	T11N 1915
		and raise a mound of stone, 2 ft. base, $l\frac{1}{2}$ ft. high S.
		of cor. Land, rolling, exposure and drainage to NW. Soil, coarse gravel and light sandy loam, with scattering rocks, on gravel and hard, tough, reddish clay subsoils; 2nd rate. Undergrowth, short greasewood, shadscale and bunch grass. No timber. Grazing land.
		July 19: For solar see line bet. secs. 25 and 36. From corner of sections 27, 28, 33 and 34, I run West, on sectional correction line, bet. secs. 28 and 33.
	1.80 16.20 27.60 34.15 40.00	Over rolling land, sloping SW. Ravine, 10 ft. deep, course SW. Ravine, 15 ft. deep, course SW. Ravine, 15 ft. deep, course SW. Wash, 30 lks. wide, 2 ft. deep, course SW. 65 ft. below sec. cor. Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for ½ sec. cor., with brass cap mkd.,
		<u>, S28</u> * S33
		1915
	47:95 59.90 72.10 80.00	and raise a mound of stone, 2 ft. base, $l\frac{1}{2}$ ft. high N. of cor. Ravine, 20 ft. deep, course S. Ravine, 20 ft. deep, course SW. Ravine, 10 ft. deep, course SW. 35 ft. below $\frac{1}{4}$ sec. cor. Set an iron post 3 ft. long, 2 ins. in dia., 24 ins. in the ground for cor. of secs. 28,29,32 and 33, with brass cap mkd.,
1	-	