


Resurvey E. Boundary of T. 19 N., R. 36 E.

7.

Chains

From which
 A pinon pine, 16 ins. in diam., bears S. 76° 15'E. 28 lks.
 dist. mkd., $\frac{1}{4}$ S7 BT
 A Pinon Pine, 13 ins. in diam., bears S. 67° 30'W. 44 lks.
 dist. mkd., $\frac{1}{4}$ S12 BT
 48.35 Top of spur and leave slide rock, 210 ft. above $\frac{1}{4}$ sec.
 cor. this spur is approximately 1220 ft. above the tp.
 cor. Spur projects E., descend along E. slope to
 61.00 Spur, projects N. 20°E., thence descend steep N.W. slope.
 80.00 On N. slope, near S. edge of canyon, 710 ft. below spur
 at 48.35 chs.
 Set an iron post, 3 ft. long, 3 ins. in diam., 24 ins. in
 the ground for cor. of secs. 1, 6, 7 and 12, with brass
 cap mkd.,



1916

From which
 A Pinon Pine, 14 ins. in diam., bears S. 72°W. 54 lks.
 dist., mkd T19N R36E S12 BT
 A Pinon Pine, 14 ins. in diam., bears N. 67° 50'W., 52 lks.
 dist. mkd., T19N R36E S1 BT
 A Pinon Pine, 8 ins. in diam., bears N. 86°E., 46 lks.
 dist. mkd. T19N R37E S6 BT
 A Pinon Pine, 6 ins. in diam., bears S. 35°E., 31 lks.
 dist. mkd., T19N R37E S7 BT
 Land, high rough mountains, general face and drainage to
 the E.
 Soil, rocky and gravelly, 3rd. and 4th rates.
 Timber, dense pinon pine and cedar; undergrowth, sage
 brush.

0.90 N. 0° 27'E. bet. secs. 1 and 6.
 Over high, rough mountainous land, through scattering
 pinon pine and cedar.
 Canyon and small stream of water, 10 ft. below corner.
 course E., canyon 2 chs. wide.
 Ascend steep S. and S.W. slope, 620 ft.
 26.15 Ridge, cross at small peak, bears E. and N. 80°W., 6
 chs. to saddle thence N.W. Descend 60 ft.
 30.40 Head of draw, course N. 80°E., ascend S.E. slope, 130
 ft. to
 36.10 Small spur, slopes E. descend 10 ft. to
 38.90 Small ravine, course S.E., ascend S. slope 30 ft.
 40.00 Set an iron post, 3 ft. long, 1 in. in diam., 24 ins.
 in the ground for $\frac{1}{4}$ sec. cor., with brass cap mkd.,



1916

From which
 A Pinon Pine, 9 ins. in diam., bears N. 27° 15'E. 47 lks.
 dist. mkd., $\frac{1}{4}$ S 6 BT
 A Pinon Pine, 7 ins. in diam., bears S. 72°W., 68 lks.
 dist. mkd. $\frac{1}{4}$ S1 BT
 Continue ascent of S. slope, 310 ft.
 53.65 High ridge, bears E. and W., Descend steep N. slope.
 64.20 Head of canyon, course N.E., 540 ft. below ridge.
 Ascend along rocky E. slope.
 80.00 Intersect the S. bdy. of T. 20 N., R 36 E., at N. 89°
 54'W. 1.84 chs. from the cor. of T. 20 N., Rgs. 36
 and 37 E.
 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins.
 in the ground for cor. of T. 19 N., Rgs. 36 and 37 E.,