


Chains	
	post available to set.
46.00	Spur, 30 ft. above $\frac{1}{4}$ sec. cor., projects N. 20° E.; descend NE. slope, 255 ft.
50.75	Deep draw, course N. ascend NW. slope.
63.00	Enter narrow strip of timber, bears NW. 5 chs.; and SE. 3 chs.
67.80	Top of ascent on N. slope, 215 ft. above draw, bears S. leave timber, bears N. and S.; descend along NE. slope, 165 ft.
77.40	Near mouth of draw, course N. 8 chs. to main canyon. Ascend 50 ft. to
82.72	The cor. of secs. 5, 6, 7 and 8. Land, rough mountains, general N. face and drainage. Soil, stony, and gravelly, mixed with fine, rich, sandy and black mountain loams; 2nd and 3rd. rates. Timber, pinon pine on 4.80 chs.; undergrowth, sage brush and grass. Grazing land.

Nov. 3, 1915.

	Nov. 4: At 8h 14m a.m., l.m.t., I set off $39^{\circ} 36'$ on the lat. arc; $15^{\circ} 9'S$ on the decl. arc; and determine a meridian at the above cor., thence N. $0^{\circ} 3'W$. on a true line bet. secs. 5 and 6. Over rolling mountainous land, general face to the W., through heavy sage brush undergrowth. Descend 75 ft.
3.10	Wash, 20 lks. wide, 2 ft. deep, in bottom of canyon, 5 chs. wide. Ascend 120 ft.
15.15	Spur, projects N. $80^{\circ}W$.; descend N. slope, 80 ft.
17.90	Deep draw, course W. to NW.; ascend SW. slope, 120 ft.
23.60	Ridge, bears E. and NW.; enter few scattering trees, bears E. and W.; descend NE. slope, 360 ft.
37.60	Enter canyon, course W.
40.00	On N. edge of canyon, bears N. $80^{\circ}E$. and W. Set a porphyry stone, 26x12x9 ins., 15 ins. in the ground, marked $\frac{1}{4}$ on W. face; from which A Pinon Pine, 9 ins. in diam., bears S. $46\frac{1}{2}^{\circ}E$., 273 lks. dist. mkd., $\frac{1}{4}$ S5 BT and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of corner. No trees within limits in sec. 6. No iron post available to set; leave all timber, bears E. and W. Ascend SW. slope, 185 ft.
51.65	Spur, projects S. $70^{\circ}W$.; descend NW. slope, 105 ft.
69.50	Head of draw, course SW. for 3 chs., thence S. $80^{\circ}W$.; ascend steep SE. slope, 200 ft.
77.00	Rocky ridge, bears SW. and NE.; thence gently ascend W. slope, 10 ft. to
81.96	Intersect 4th Standard Parallel N., 8.06 chs., E. of the standard corner of secs. 31 and 32, T. 21 N., R. 36 E., which is a limestone, 12x14x8 ins. above ground, firmly set, properly marked. No accessories. I raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of cor. At point of intersection, set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground, for closing corner of secs. 5 and 6, with brass cap mkd.,



and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of cor.