


Resurvey of fractional subdivision, T 21 N, R 29 E.

Chains ground for cor. of secs. 4, 5, 8 and 9, with brass cap mkd.




dig pits 18 x 18 x 12 ins. in each sec., $5\frac{1}{2}$ ft. dist.

From the cor. of secs. 4, 5, 8 and 9.

E. bet. secs. 4 and 9.

40.00 Set an iron post, 3 ft. long, 1 in. dia., 24 ins. in the ground for $\frac{1}{4}$ sec. cor. with brass cap mkd.



dig pits 18 x 18 x 12 ins. E. and W. of post, 3 ft. dist.

From cor. of secs. 4, 5, 8 and 9.


N $0^{\circ}17'E$, bet. secs. 4 and 5.

40.05 The old $\frac{1}{4}$ sec. cor.

Reestablish this cor. as follows:

At the same point,

Set an iron post, 3 ft. long, 1 in. dia., 24 ins. in the ground for $\frac{1}{4}$ sec. cor, with brass cap mkd.



dig pits 18 x 18 x 12 ins., N. and S. of post, 3 ft. dist. and set the old cor. alongside of post.

Thence N $1^{\circ}3'W$

80.00 The old corner of secs. 4, 5, 32 and 33, on the N. bdy. of the tp.

Reestablish this cor. as follows:

At the same point,

Set an iron post, 3 ft. long, 2 ins. dia., 24 ins. in the ground for cor. of secs. 4, 5, 32 and 33; with brass cap mkd.