

Subdivision of T.5 S., R.66 E.

Chains

40.00 Note: As it was impossible to get pack horse with iron posts and necessary tools with which to set them, to this point, and to avoid future delay in the work, in place of iron post, set a sandstone, 4x8x14 ins., 10 ins. in the ground for $\frac{1}{2}$ sec. cor., marked $\frac{1}{2}$ on W. face; no suitable bearing trees available; raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W. of cor.

Cor. stands 225 ft. above head of canyon.

40.70 Top of ascent, 40 ft. above $\frac{1}{2}$ sec. cor., bears S.35°E. and W.

Thence nearly level along top of mountain.

43.50 Point of steep descent, bears NE. and SW.

51.80 Head of canyon, 240 ft. below point of steep descent, drains S.60°W.

Ascend steeply.

59.10 Top of steep ascent and top of mountain, 250 ft. above head of canyon, bears NW. and S.60°E.

Thence nearly level along top of mountain.

80.80 Intersect the First Standard Parallel South, 20.80 chs. S.89° 21'W. of the standard cor. of secs. 35 and 36, heretofore described.

Set an iron post, 3 ft. long, 2 ins. in dia., 6 ins. in the ground, to solid rock and erect a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, around post for C.C. of secs. 1 and 2, with brass cap marked

T4S R66E
S35

S2 S1
T5S R66E

C C

1916

No suitable bearing trees available; raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

Land, rugged and mountainous with a general exposure and drainage to the W.; soil, stony, of porphyry and sandstone formation; 4th rate; timber, scattering growth of scrub cedars; scattering undergrowth of sage brush, jun-