

Subdivisions of T. 41 N., R. 31 E.

Chains W. of cor.  
 81.55 The cor. of sec. 4, 5, 32 and 33 on the N. bdy., heretofore described.  
 Land, desert. Soil Gumbo. Some greasewood. No timber.


Subdivisions of T. 41 N., R. 31 E.

-----  
 From the standard cor. of secs. 35 and 36, which is a 3 in. iron post, 12 ins. above ground, firmly set, marked and witnessed as described by the surveyor general.

N. 0° 01' W. bet. secs. 35 and 36.


Over mountainous land. ascend E. slope broken rock cliff.

1.36 Top of ascent 40 ft. above standard cor.; descend steep broken NE. slope, scattered scrub junipers.  
 19.50 Top of rocky spur, 470 ft. below standard cor., bears S. 30° W. and projects N. 40° E. 6 chs., thence N.; descend steep NW. slope 720 ft. to the  $\frac{1}{4}$  sec. cor.  
 40.00 Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor., with brass cap mkd.



and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

42.00 Dry gulch, course N. 25° W.; descending along NW. slope.  
 54.00 Deer creek, running water, 4 lks. wide, 12 ins. deep, in bottom of canyon, course N. 70° W., 240 ft. below  $\frac{1}{4}$  sec. cor.; ascend steep S. slope.  
 62.30 Top of low spur, projects S. 40° W.; ascend along W. slope.  
 72.70 Top of rocky spur, 450 ft. above bottom of canyon, projects W.; descend steep N. slope 240 ft. to the sec. cor.  
 80.00 Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground for the cor. of secs. 25, 26, 35 and 36, with brass cap mkd.



and raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$  ft. high, W. of cor.

Land, rough broken mountains, drainage to the west.

Soil, shallow brown clay, loose slide rock on steep slopes,