

Fractional Resurvey of Subdivision Lines of T. 47 N., R. 32 E., 9.

Chains  
 51.80 Ravine, course NW; ascend 45 ft. on SW. slope to top of spur.  
 56.40 Spur, projects N.60°W.; descend 45 ft. on NW. slope to ravine.  
 59.10 Ravine, course N.60°W.; ascend 130 ft. on SW. slope to top of spur.  
 68.00 Spur, projects N. 55°W.; descend 55 ft. on NW. slope to ravine.  
 73.60 Ravine, course N.80°W.; ascend 40 ft. on SW. slope.  
 78.00 Top of ascent; descend 15 ft. on NW. slope to cor.  
 81.76 The cor. of secs. 3, 4, 9 and 10, which I find to be a trapstone, 14x8x7 ins., standing in a mound of stone, 2 ft. base, 6 ins. high, but with no marks discernible, and which I reestablish as the cor. of secs. 4 and 9 by setting the stone 9 ins. in the ground and setting alongside of it an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, with brass cap mkd.,




and raise a mound of stone, 2 ft. base, 1½ ft. high W. of corner.  
 Land, mountainous. Soil, stony and gravelly, Good sagebrush and bunchgrass. No timber.

N. 0° 32' W. on E. bdy. of sec. 4.


Over mountainous land. Descend 140 ft. to draw, starting on NW. slope.

14.00 Slope changes to NE.  
 21.55 Draw, course NW.; ascend 70 ft. on SW. slope.  
 30.50 Top of ascent; descend 30 ft. on NW. slope to ¼ sec. cor.  
 41.43 The ¼ sec. cor., which I find to be a granite stone, 16x11x9 ins., lying on top of the ground and in a mound of stone, 3 ft. base, 1 ft. high, and marked ¼ on top face, and which I reestablish as the ¼ sec. cor. referring to sec. 4 by setting the stone 11 ins. in the ground with the mark to the W., setting alongside of it an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for ¼ sec. cor. with brass cap mkd.,



and raise a mound of stone, 2 ft. base, 1½ ft. high W. of cor. At this cor. my course changes to N. 0° 55' E.

48.59 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for ¼ sec. cor., with brass cap mkd.,



and raise a mound of stone, 2 ft. base, 1½ ft. high E. of cor. NOTE On July 25, 1916, in accordance with Supplemental Special Instructions dated January 24, 1916, I change the marking on the above ¼ cor., set Nov. 10, 1915 by W. E. Hoffman for a cor. of secs. 3 and 4, so as to refer to sec. 4 only and mark the cor. as shown above. At a point 7.16 chs. N. 0° 55' E. of the ¼ cor. for sec. 4 I set the ¼ cor. for sec. 3.

H. W. Reppert, U.S. Surveyor.

81.79 The old Closing Corner of secs. 3 and 4, which I find to be a talc stone, 18x7x6 ins., lying on top of the ground, surrounded by stones and marked with 6 grooves on S. and 3 grooves on E. face. As this is not on the State Line, I change it to a line point by effacing the grooves and chiseling LR on the S. face.

At this point my course changes to North.

128.08 Intersect the Nevada-Oregon State Line at a point 16.93 chs. S. 88° 37' W. of the 222 mile cor., and at point of intersection set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground, for Closing Corner of secs. 3 and 4, with brass cap mkd.,

