

Subdivisions of T. 27 N., R. 44 E.

49

Chains

15.00 Top of ridge, 10 ft. above dry wash, bears S. 80°W. and N. 80°E.; Descend over rolling W. slope.
 24.00 Bottom of draw, and wash, 20 lks. wide, 3½ ft. deep, 130 ft. below top of ridge, course S. 45°W.; descend along S. slope.
 28.45 Same draw and wash, course N. 65°W.; ascend.
 40.00 Set an iron post, 3 ft. long, 1 in. diam., 20 ins. in the ground to solid rock and in a mound of stone, for ¼ sec. cor., with brass cap mkd.,

S19 ½
 S30
 1915

and raise a mound of stone, 2 ft. base, 1½ ft. high N. of corner.

Top of spur, 15 ft. above draw, projects N.; descend rolling W. slope, 160 ft. to the closing corner.

54.00 Dry wash, course S. 45°W.; turning N. W.

57.70 Dry wash, course N. 45°W.; descend rolling W. slope.

77.38 Intersect W. bdy., 92 lks. S00° 20'W. of the cor. of secs. 24 and 25 T. 27 N., R. 43 E. At the point of intersection I build a cor. as follows:

Set an iron post 3 ft. long, 2 ins. diam., 24 ins. in the ground for closing corner of secs. 19, and 30 with brass cap mkd.,

T27N
 R43E | R44E
 S24 |
 S25 | S19
 C |
 C |
 S30
 1915

and raise a mound of stone, 2 ft. base, 1½ ft. high E. of corner.

Land, W. slope of valley rolling.

Soil, rocky, gravelly and stony clay loam, 14 ins. deep, rocky clay subsoil.

Undergrowth, sagebrush, shadscale, browse and bunch grass
 No timber.

N. 0° 04'W. bet. secs. 19 and 20.

Over rolling land, gradually descend.

2.30 Dry wash, 20 lks. wide, 3 ft. deep, course W. 2chs., thence S. 60°W.; ascend.

6.86 Top of ridge, 45 ft. above dry wash, bears N. 70°E. and S. 70°W.; descend rolling W. slope 95 ft. to the ¼ sec. cor.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for ¼ sec. cor., with brass cap mkd.,

S19 ½ | S20
 1915

and raise a mound of stone, 2 ft. base, 1½ ft. high W. of corner.

Gradually descend rolling W. slope.

52.00 Dry wash, course W.

72.00 Bridle trail, bears N. 80°E. and S. 80°W.

75.00 Dry wash, 30 lks. wide, 4 ft. deep, 70 ft. below ¼ sec. cor., course W.; ascend 60 ft. to the sec. cor.

77.50 Telephone line from Battle Mountain to Austin and Manhattan, bears N. 80°E. and S. 80°W.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground for cor. of secs. 17, 18, 19 and 20, with brass