

Chains

and raise a mound of stone, 2 ft. base, 1½ ft. high N. of corner.


Gradually descend 225 ft. to the closing corner.

42.20 Descend along S. W. slope.

76.87 Intersect W. bdy. 94 lks. S. 0° 17' W. of the cor. of secs. 13 and 24 of T. 27 N., R. 44 E., At the point

of intersection I build a corner as follows:

Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground for closing corner of secs. 18 and 19 with brass cap mkd.,



and raise a mound of stone, 2 ft. base, 1½ ft. high E. of corner.

Land, rolling W. slope.

Soil, gravelly, stony and rocky, dark brown clay, 8 ins. deep, rocky, clay subsoil, loose broken rock on surface.

Undergrowth, sagebrush, browse, shadscale and bunch grass. No timber.

June 7, 1915.

Surveyed by W.R. Johnston.

June 8, 1915: At 8h. 00m., a.m., l.m.t., I set off 40° 11½' N. on the lat. arc; 22° 48½' N. on the decl. arc and determine a meridian with the solar at the cor. of secs. 17, 18, 19 and 20.

Thence I run

N. 0° 04' W. bet. secs. 17 and 18.

Over W. slope rolling land, gradually ascend.


4.30 Top of bench bears E. and W.; 50 ft. above sec. cor., gradually ascend.

17.39 Top of bench 15 ft. above S. edge, gradually descend N. W. slope.

33.50 Bottom of ravine, 230 ft. below top of bench, course W.; ascend.

39.90 Top of bench, bears E. and W.; 80 ft. above ravine, gradually descend.

40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for ¼ sec. cor., with brass cap mkd.,



and raise a mound of stone, 2 ft. base, 1½ ft. high W. of corner.

Gradually descend.

59.90 Foot of descent, 50 ft. below ¼ sec. cor., gradually ascend.

66.17 Top of spur, 120 ft. above foot of descent, projects S. 75° W.; descend.

73.00 Bottom of gulch, 105 ft. below top of spur, course W.; ascend 20 ft. to the sec. cor.

80.00 Set an iron post, 3 ft. long, 2 ins. diam., 24 ins. in the ground for cor. of secs. 7, 8, 17 and 18, with brass cap mkd.,

