

Chains.

and raise a mound of stone, 2 ft. base, 1½ ft. high, W. of cor.  
No trees near for marking.  
Land, mountainous, steep slopes and broken spurs.  
Soil, heavy clay loam, shallow and very rocky; surface covered with red shale rock and granites, exposed barren ledges.  
Timber, few scattered pines and junipers.  
Undergrowth, sagebrush and scant growth of grass.

- West, on a true line bet. secs. 6 and 31.  
Over mountainous land, ascend.  
4.00 Top of ridge, 35 ft. above cor., bears N. 45° E. and S. 45° W.; descend.  
21.83 Ravine, 345 ft. below top of ridge, course N. 50° W.; ascend SE. slope.  
33.78 Top of ridge, 65 ft. above ravine, bears N. 80° W. and S. 80° E.; descend, 130 ft. to the ¼ cor.  
40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for ¼ sec. cor., with brass cap marked:

S 31 ¼

S 6

1915

- and raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.  
Descend SW. slope, rolling land.  
63.44 Wash, 30 lks. wide, 3 ft. deep, course S. 30° W.; 330 ft. below top of ridge; ascend.  
70.57 Top of spur, 115 ft. above wash, projects S.; descend.  
94.86 Foot of W. slope 30 ft. below top of spur; enter valley land.  
134.40 Intersect the E. bdy. of T. 19 N., R. 45 E., 20.10 chs. N. 0° 05' E. of the SE. cor. of T. 19 N., R. 45 E. previously described.  
At the point of intersection I build a cor. as follows:  
Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground, for closing cor. of Tps. 18 and 19 N., R. 46 E. with brass cap marked;

T19N

R45E

R46E

S31

C

C

S36

S6

S1

R45E

R46E

T18N

1915

and raise a mound of stone, 2 ft. base, 1½ ft. high, E. of cor.  
Land, mountainous, rolling and valley.  
Soil, on ridges, very stony and rocky, heavy clay loam, barren outcrops; W. 40.00 chs. W. slope valley with a stony and gravelly light clay loam soil, medium texture, some loose and imbedded boulders washed from foothills covering surface.  
Undergrowth, sagebrush and some bunch grass.  
No timber.

Sept. 1, 1915.