

## 6. Resurvey of 4th Standard Parallel thru R. 47 E.

## Chains

- ard  $\frac{1}{4}$  sec. cor. of sec. 32 which is a granite stone 2x8x16 ins. set in mound of stone, marked and witnessed as described by the Surveyor General I destroy the old corner and its accessories.
- 55.21 Top of low spur, projects N. 40°W.; descend.
- 63.33 Bottom of canyon 770 ft. below high spur, at 26.00 chs. course N.; ascend steep rocky E. slope.
- 76.84 Top of ridge, 390 ft. above canyon, bears N. and S.; descend through pinon pine timber 50 ft. to the Standard Corner.
- 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 24 ins. in the ground for cor. of secs. 31 and 32, with brass cap mkd.;

T21NR47E

S31 | S32

1915

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high N. of corner; from which

A Pinon Pine, 10 ins. diam., bears N. 40° 30'E. 34 lks. dist. mkd. T21NR47ES32BT

A Pinon Pine, 9 ins. diam., bears N. 54° W., 46 lks. dist. mkd. T21NR47ES31BT

Land, mountainous.

Soil, shallow and rocky heavy clay loam, stiff and compact, mixed with decomposed granites with exposed ledges of same.

Undergrowth, sagebrush and fair growth grass.

Timber, pinon pine and juniper.

- W. on a true line along the S. bdy. of sec. 31. Over mountainous land descend W. slope through heavy timber.
- 16.50 Bottom of gulch 410 ft. below sec. cor., course N. 60°W.; ascend.
- 23.97 Top of small spur 40 ft. above gulch, projects N. 40°W.; descend.
- 32.78 Bottom of canyon 520 ft. below top of spur, wash in bottom 20 lks. wide, 6 ft. deep, course N.; ascend.
- 37.62 Wood road, bears N. and S.
- 40.00 Set an iron post, 3 ft. long, 1 in. diam., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor., with brass cap mkd.,

S31  $\frac{1}{4}$ 

1915

- and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high N. of corner; from which
- A Pinon Pine 10 ins. diam., bears N. 34°E., 82 lks. dist. mkd.  $\frac{1}{4}$ S31BT
- Corner on top of low spur, 23 ft. above canyon, projects N. 40°W.; descend.
- 47.50 Wood road, bears N. 70°E. and S. 70°W.; ascend W. slope of mountain through pinon pine and juniper timber, 470 ft. to the St. Tp. corner.
- 50.00 No traces of the old Standard corner found after careful search.
- 80.00 Set an iron post, 3 ft. long, 3 ins. diam., 20 ins. in the ground to solid rock and in a mound of stone for cor. of secs. 31 and 36, with brass cap mkd.,

T21N

R46E | R47E

S36 | S31

1915

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high N. of corner.