

30.

## Subdivisions of T. 20 N., R. 47 E.

Chains

 $\frac{1}{2}$ S3 | S2

1915

and raise a mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high W. of corner.

No trees near for marking.

51.90 Top of spur, projects W., 70 ft. below ridge, descend N. W. slope.

71.64 Bottom of ravine, 140 ft. below top of spur, course N.  $60^\circ$  W.; ascend 70 ft. to the closing corner.

80.36 Intersect the 4th Standard Parallel North, 32.33 chs. E. of the Standard Corner of secs. 34 and 35 of T. 21 N., R. 47 E. heretofore described. At the point of intersection I build a corner as follows:

Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in the ground for closing cor. of secs. 2 and 3, with brass cap mkd:

T21NR47E

S34 | S35

S 3 | S2

1915

and raise a mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high S. of corner.

From which

A Pinon Pine 6 ins. in diam., bears S.  $32^\circ 30' W.$ , 31 lks. dist. mkd. T20NR47ES3BT

A Pinon Pine 6 ins. in diam., bears S.  $32^\circ 15' E.$ , 39 lks. dist. mkd. T20NR47ES2BT

Land, mountainous.

Soil, light brown clay loam, very rocky, surface covered with loose granite rock, some exposed granite ledges on spurs and ridges.

Undergrowth, sagebrush and good growth bunch grass.

Timber, pinon pine and mountain mahogany.

Aug. 10, 1915.

Surveyed by H.W. Reppert.

Aug. 6, 1915: At 8h. 15m., a.m., l.m.t., set off  $39^\circ 33' N.$  on the lat. arc;  $16^\circ 54' N.$  on the decl. arc; determine a meridian with the solar at the cor. of secs. 3, 4, 33 and 34 on the S. bdy., heretofore described.

Thence I run

N.  $0^\circ 02' W.$  bet. secs. 33 and 34.

Over mountainous land, ascend S. slope.

9.80 Top of spur, 70 ft. above sec. cor., projects E.; desc.

15.55 Wash in bottom of canyon, 20 lks. wide, 3 ft. deep, 65 ft. below spur, course S.  $30^\circ E.$ ; ascend S.W. slope, 300 ft. to the  $\frac{1}{4}$  sec. cor.

35.05 Ravine, course S.  $40^\circ E.$ ; ascend.

40.00 Set an iron post 3 ft. long, 1 in. in diam., 10 in. in the ground to solid rock and in a mound of stone for  $\frac{1}{4}$  sec. cor., with brass cap mkd.;

 $\frac{1}{4}$  | S33 | S34

1915

and raise a mound of stone 2 ft. base,  $1\frac{1}{2}$  ft. high W. of corner.

43.67 Top of spur, 365 ft. above canyon, projects S.  $40^\circ W.$ ; desc.

51.05 Ravine, course S.  $60^\circ W.$ ; ascend along steep W slope.

56.36 Top of spur, 520 ft. above canyon, projects S.  $70^\circ W.$ ; desc.

64.36 Ravine, course W.; ascend.

72.50 Top of spur, 705 ft. above canyon, projects S.  $75^\circ W.$ ; asc. along W. slope.