

Subdivisions of T. 20 N., R. 47 E.

Chains

29.00

Bottom of draw near head 140 ft. below top of ridge, course S.40°E.; ascend through scattering timber.

40.09

Set an iron post 3 ft., long 1 in. in diam., 26 ins. in the ground for 1/4 sec. cor., with brass cap mkd.:

S3 1/4
S10
1915

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high N. of corner.

From which

A Pinon Pine, 6 ins. in diam., bears N.23°E., 26 lks. dist. mkd. 1/4S3BT

A Mountain mahogany, 10 ins. in diam., bears S.84°W., 76 lks. dist. mkd. 1/4S10BT

Ascend 45 ft. to top of ridge, through timber.

42.80

Top of ridge, 170 ft. above head of draw, bears N.40°W. and S.40°E., descend.

51.20

Leave heavy timber, gradually descend.

54.70

Wash 20 lks. wide, 3 ft. deep, course S.75°E.; ascend gradual slope 160 ft. to the sec. cor.

58.30

Road from Monitor valley to Grass valley, bears N. and S.

80.18

The cor. of secs. 3, 4, 9 and 10.

Land, mountainous.

Soil, ridges with shallow and very rocky light brown clay loam with exposed ledges; draws and ravines with deep rich dark loam 10 to 15 ins. deep, compact clay subsoil

Undergrowth, sagebrush and good growth bunch grass.

Timber, pinon pine and mountain mahogany.

Not on meridian for observation for latitude on this date.

Aug. 10, 1915.

Surveyed by H.W.Reppert.

Aug. 9, 1915. For solar on this date see line between secs. 10 and 15.

N.0° 02'W, on a true line bet. secs. 3 and 4.

Over rolling and mountainous land, gradually ascend through scattering timber.

1.60

Top of low spur, 5 ft. above sec. cor., bears E. and W., descend.

19.16

Bottom of ravine, 10 ft. below top of spur, course E.; ascend.

37.00

Top of the main dividing ridge, between Monitor and Grass valleys 50 ft. above ravine, bears E. and W.; desc.

40.00

Set an iron post 3 ft. long, 1 in. in diam., 26 ins. in the ground for 1/4 sec. cor., with brass cap mkd.:

S4 1/4 | S3
1915

and raise a mound of stone 2 ft. base, 1 1/2 ft. high W. of corner.

From which

A Pinon Pine 6 ins. in diam. bears N.22°30'W., 38 lks. dist., mkd. 1/4S4BT

A Pinon Pine 8 ins. in diam., bears S.89°E., 68 lks. dist. mkd. 1/4S3BT

Ascend along E. slope.

48.80

Top of spur, 20 ft. above 1/4 sec. cor., projects E.; desc.

52.90

Bottom of ravine, 55 ft. below top of spur, 15 lks. wide, 4 ft. deep, course E.; ascend.

68.70

Top of E. slope 100 ft. above ravine, descend N.E. slope.

80.28

Intersect the 4th Standard Parallel 32.22 chs. E. of the Standard Corner of secs. 33 and 34 of T. 21 N., R.47 E heretofore described. At the point of intersection I build a corner as follows:

Set an iron post 3 ft. long, 2 ins. in diam., 24 ins. in