```
12.
             Resurvey of West Boundary of T. 22 N., R. 48 E.
Chains
             Bottom. of canyon, 110 ft. below sec. cor., wash in bottom of canyon, 12 lks. wide, 2 ft. deep, course N. 80°W.;
 9.50
             ascend.
             Top of ridge, 200 ft. above canyon, bears N. 20°W. and S. 20°E.; descend through scattered pines.
Bottom of canyon, with wash, 10 lks. wide, 2 ft. deep,240 ft. below top of ridge, course N. 80°W.; ascend.
Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground, for \(\frac{1}{4}\) cor. to secs. 13 and 18, with brass
22.10
34.90
40.00
             cap marked:
                                         S 13 1 S 18
                                                    1915.
             and raised a mound of stone, 2 ft. base, 1\frac{1}{2} ft. high W.
             of cor.
             From which
             A pinon pine, 20 ins. in dia., bears S. 70° 15'W. 33 lks. dist. marked: \(\frac{1}{4}\) S 13 BT

A pinon pine, 7 ins. in dia., bears N. 83° 30'E. 34 lks. dist. marked: \(\frac{1}{4}\) S 18 BT

Top of ridge, 180 ft. above canyon, bears E. and W.; descend through scattered pines and junipers.

Bettom of gulah 170 ft. below top of ridge. course N.
 48.60
               Bottom of gulch, 170 ft. below top of ridge, course N.
 59.80
             30°W.; ascend.
             Top of spur, projects W., 50 ft. above gulch, descend. Bottom of ravine, 50 ft. below top of spur, course W.;
  66.00
  69.90
              ascend.
             Top of ridge, 130 ft. above ravine, bears N. 70°E. and
  77.40
              S. 70°W.; descend, 20 ft. to the sec. cor. along NW.
              slope.
              Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. i the ground, for cor. to secs. 7, 12, 13 and 18, with
                                                                                              24 ins. in
  80.00
              brass cap marked:
                                       T 22 N
R 47 E. R 48 E
S 12 S 7
                                              S 13 | S 18
                                                     1915
              and raised a mound of stone, 2 ft. base, l\frac{1}{2} ft. high, W.
             of cor.
No trees near for marking.
              Land, mountainous. Soil, loose, rocky light clay loam; loose and imbedded
              quartzite rock on surface; some exposed outcrops.
              Undergrowth, sagebrush, service brush and some grass.
Timber, dense pinon pine on S. half mile; balance, scat-
              tering growth.
                         RESURVEY OF W. BDY. OF T. 22 N., R. 48 E.
              N. on a true line bet. secs. 7 and 12.
              Over mountainous land, descend.
              Top of spur projects N. 70°W.; descend.
Ravine, 4 lks. wide, 1 ft. deep, 220 ft. below top of spur, course N. 70°W. 5.00 chs., thence S. 70°W.;
  4.96
12.80
              ascend.
              Top of ridge, 50 ft. above ravine, bears E. and W.;
23.00
              The old 4 cor. of secs. 7 and 12, heretofore described. and hereafter referring to a cor. of sec. 12 of T. 22 N. R. 47 E. only. I establish a new cor. alongside the
              descend.
29.40
              old cor. as follows: , bast aponishmon
```