

Resurvey, Ruby Valley Guide Meridian, T. 8 N., Rs. 55 and 56 E. 7

Chains

1/4 S12	
---------	--

1915

Dig pits, 18x18x12 ins., N. and S. of post 3 ft. dist., and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high W. of cor.

41.94

Old road, Locke's Ranch to Blue Eagle, bears NE. and SW.

42.07

By proportional measurement.

Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for 1/4 cor. of sec. 7, with brass cap mkd.,

1/4 S7	
--------	--

1915

Dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist., and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high W. of cor.

80.00

Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground for cor. of secs. 1 and 12, with brass cap mkd.,

T8N

R55E | R56E

S1

S12

1915

and raise a mound of stone, 2 ft. base, 1 1/2 ft. high W. of corner.

Land, slightly rolling with general drainage to SE. and S.

Soil, white and dark alkali mixed with a white sandy clay of medium texture, 26 ins. deep.

No timber; scattering greasewood and shadscale; very scant grazing, 80 chs.

N. 0° 16' E. bet. secs. 1 and 6.

Slightly rolling land, scattering greasewood and shadscale.

2.30

By proportional measurement.

Set an iron post, 3 ft. long, 3 ins. in dia., 24 ins. in the ground for cor. of secs. 6 and 7, with brass cap mkd.,

T8N

R55E | R56E

S6

S7

1915

Dig pits, 24x24x12 ins., in each sec. 6 ft. dist., and raise a mound of earth 4 ft. base, 2 ft. high W. of cor.

31.14

Wagon road, Tonopah to Currant, bears NE. and SW.

40.00

Set an iron post, 3 ft. long, 1 in. in diam., 26 ins. in the ground for 1/4 cor. of sec. 1, with brass cap mkd.,

1/4 S1	
--------	--

1915

Dig pits, 18x18x12 ins., N. and S. of post 3 ft. dist., and raise a mound of earth 3 1/2 ft. base, 1 1/2 ft. high W. of cor.

42.53

Intersect old 1/4 cor. of sec. 6, heretofore described.

82.73

Intersect the cor. of Tps. 8 and 9 N., Rs. 55 and 56 E., heretofore described.

In exact position of this old Tp. cor., set an iron