

Retracement and resurvey of portion of subs. of T. 20 N., R. 24 E.  
Retracement of portion of W. and N. bdy. T. 20 N., R. 24 E. 9

Chains

5 and 8.

From the cor. of secs. 5, 6, 7 and 8, I run  
S. 89° 21' W. on a true line bet. secs. 6 and 7.

40.17½ The proportionate distance for the reestablished ¼ sec.  
cor.

Set an iron post 3 ft. long, 1 in. diam., 26 ins. in the  
ground for ¼ sec. cor., with brass cap mkd.,

S6 ¼  
S7  
1916

and raise a mound of stone 2 ft. base, 1½ ft. high N.  
of corner.

80.65 The corner of secs. 1, 6, 7 and 12.

May 3, 1916.

Retracement of portion of W. and N. Bdy. T. 20 N., R. 24 E

May 2, 1916: For solar on this date see retracement of  
line bet. secs. 8 and 17.

From the cor. of secs. 1, 6, 7 and 12 on the W. bdy.,  
heretofore described—I retrace

N. bet. secs. 1 and 6.

40.08 Intersect E. and W. line at a point 66 lks. E. of the ¼  
cor. of secs. 1 and 6, which is a basalt stone, 7x14x16  
ins. above ground, firmly set, marked and witnessed as  
described by the Surveyor General. This ½ mile bears  
N. 0° 57' W. and its true length is 40.08 chs. I continue  
my retracement N. along same line.

80.43 Intersect E. and W. line, 94 lks. E. of the old Standard  
Corner of Tps. 20 and 21 N., Rs. 23 and 24 E., which is  
a basalt stone, 7x14x16 ins. above ground, firmly set,  
marked and witnessed as described by the Surveyor General.  
This last half mile bears N. 0° 24' W. and its true length  
is 40.35 chs.

From the Standard corner of Tps. 20 and 21 N., Rs. 23  
and 24 E. I run S. 89° 35' E. on retracement bet. secs.  
6 and 31.

40.08 Intersect N. and S. line at a point 8 lks. N. of the  
old ¼ cor. of secs. 6 and 31, which is a basalt stone,  
10x10x14 ins. above ground, marked and witnessed as  
described by the Surveyor General. This ½ mile bears  
S. 89° 28' E. and its true length is 40.08 chs. I con-  
tinue my retracement S. 89° 35' E. along same line.

77.56 Intersect N. and S. line, 23 lks. S. of the closing cor.  
of secs. 6 and 31, which is a basalt stone, 10x14x24  
ins. above ground, marked C C on W. P L I R on E. This  
corner has been remarked with a 3 in. iron post showing  
12 ins. above ground alongside the old cor., marked and  
witnessed as described by the Surveyor General. I con-  
tinue my retracement S. 89° 35' E. along same line.

80.43 Intersect N. and S. line 25 lks. S. of the Standard Cor-  
ner of secs. 5, 6, 31 and 32, which is a trapstone,  
4x6x8 ins. above ground, firmly set, marked with 6 grooves  
on S., S.C. on N., Corner remonumented with a 1 in.  
iron post 10 ins. above ground alongside the old cor.  
with brass cap mkd.,

S C  
T21 N  
S31 | S32  
W C  
1911

Witnessed by pits and mound of earth.

This last ½ mile bears S. 89° 56' E. and its true length  
is 40.35 chs.