Subdivision of T.11 N., R.68 E.

Chains 80.00

Set an iron post, 3 ft. long, 2 ins. in dia., 24 ins. in the ground for cor. of secs. 4,5,32 and 33, with brass cap marked

T12N R68E S32 S33

1916

from Which

A pinon pine, 7 ins. dia., hears N.20° 10'E., 1.77 chs. dist., marked T 12 N R 68 E S 33 B T.

A pinon pine, 7 ins. dia., bears S.65°E., 3.42 chs. dist., marked T 11 N R 68 E S 4 B T.

A cedar, 10 ins. dia., bears N.8°W., 2.60 chs. dist., marked T 12 N R 68 E S 32 B T.

No other suitable bearing trees available; therefore raise a mound of stone, 3 ft. base, 12 ft. high, W. of cor.

Land, rolling mountainous with a general exposure and drainage to the W.; soil, brown and white coarse gravelly sandy loam of hard texture with some scattering loose lime rock on surface; timber, scattering cedars and pinon pine; medium undergrowth of sage brush, greasewood and scattering shadscale, rabbit brush and grass; fair grazing, 80 chs.

From the standard cor. of secs. 31 and 32, on the S. bdy of the Tp., heretofore described

N.0° 03'W., bet. secs. 31 and 32.

Over gently rolling land, through medium undergrowth of sage brush, greasewood, shadscale and scattering grass. 40.00 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for 4 sec. cor., with brass cap marked

> S31 | S32 1916

Dig pits, 18x18x12 ins. N. and S. of post, 3 ft. dist.