

14. Resurvey of 3rd Standard Parallel N., R. 38 E.

Chains	
	From which
	A Pinon Pine, 10 ins. in dia. bears N. $42\frac{1}{2}^{\circ}$ E., 157 lks. dist. mkd. SC $\frac{1}{4}$ S32BT
	A Pinon Pine 10 ins. in dia. bears N. $68\frac{1}{2}^{\circ}$ W., 146 lks. dist. mkd. SC $\frac{1}{4}$ S32BT
53.80	Wash, 15 lks. wide, 3 ft. deep in main ravine, 315 ft. below $\frac{1}{4}$ sec. cor. course S. 30° W.; gradually ascend general SE. slope.
60.30	Small ravine, 5 ft. deep, course S. 4 chs. to main ravine.
64.75	Low spur, 75 ft. above ravine, projects S.; descend 45 ft.
67.30	Ravine, course S. 10° E.; ascend.
75.55	The old cor., I destroy all marks on corner, and remark with A.P. for angle point cor. Thence S. $89^{\circ} 50'$ W.
80.00	On nearly S. slope, 120 ft. above ravine. Set an ironpost, 3 ft. long, 3 ins. in dia. 20 ins. in the ground to solid rock and in a mound of stone for standard corner of secs. 31 and 32, with brass cap mkd.

S	C
T16N	R38E
S31	S32
1915	

From which
A Pinon Pine, 12 ins. in dia. bears N. 75° E. 3 lks. dist mkd SC T16N R38E S32BT
A Pinon Pine, 10 ins. in dia. bears N. 54° W. $44\frac{1}{2}$ lks. dist mkd., SC T16N R38E S31BT
Land, low rolling mountains, facing and draining to the S.
Soil, gravelly and stony, mixed with some rich black mountain loam; 2nd to 4th rates.
Timber, considerable pinon pine and cedar on mile.
Undergrowth, heavy sage brush and scattering grass.
Good grazing land.

	S. $89^{\circ} 50'$ W. resurveying on S bdy sec. 31. Over rolling mountains, general face to the S., through medium dense pinon pine and cedar timber.
3.00	Low spur, 15 ft. above corner, projects S. 5 chs.; descend 20 ft.
7.00	Head of ravine, course S.; ascend 20 ft.
9.00	Low ridge, bears N. and S.; descend 70 ft.
14.05	Near head of ravine, course S.; ascend 65 ft.
19.00	Ridge bears N. 20° E. and S. 20° W.; descend general N.W. slope towards Buffalo Canyon.
24.00	Near head of ravine, 150 ft. below ridge course NW.
27.80	Near head of ravine, 225 ft. below ridge, course N.
31.30	Low spur, 30 ft. projects N. 6 chs.; descend 60 ft.
34.60	Head of ravine, course N.; ascend 30 ft.
36.80	Low spur, projects N.; descend 55 ft to
40.00	On NW slope, 310 ft. below ridge at 19 chs. Set an iron post, 3 ft. long, 1 in. in dia. 26 ins. in the ground for standard $\frac{1}{4}$ sec. cor., with brass cap mkd.,

SC
$\frac{1}{4}$ S31
1915

	From which
	A Pinon Pine, 20 ins. in dia. bears N. $13\frac{1}{2}^{\circ}$ W., 203 lks. dist. mkd SC $\frac{1}{4}$ S31BT
	No other trees within limits.
50.75	Small ravine, 240 ft. below $\frac{1}{4}$ sec. cor., course NW.; enter scattering timber, bears NW. and SE.