

W. bdy. T 23 N, R 44 E.

Chains	Begin at the cor. of Tps. 22 and 23 N, Rgs. 43 and 44 E, previously described, N. bet. secs. 31 and 36, over mountainous land with a slope to the N.W. Desc. N.W. slope.
2.70	Draw, course N 35°W, 35 ft. below tp. cor. Asc. S.W. slope.
8.05	Ridge, bears N 65°W and S 65 °E, 35 ft. above draw. Desc. N. slope.
14.00	Wash, course N 65°W, 115 ft. below ridge, Asc. S.W. slope.
21.15	Ridge, bears N 60°W and S 60°E, 150 ft. above wash. Desc. N. slope.
25.55	Wash, course N 45°W, 170 ft. below ridge. Asc. S.W. slope.
29.40	Ridge, bears N 70°W and S 70°E, 50 ft. above wash. Asc. along E. slope.
37.10,	Spur, slopes S 80°E, 80 ft. above ridge. Desc. N.E.slope.
39.70	Wash, course S 60°E, 10 ft. below spur.
40.00	Set an iron post, 3 ft. long, 1 in. dia., 24 ins. in the ground for $\frac{1}{2}$ sec. cor. with brass cap mkd.
	$\frac{1}{2}$ S 36 S 31 1916
	dig pits, 18 x 18 x 12 ins. N. and S. of post, 3 ft. dist. and raise a mound of earth $3\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high W. of cor. Asc. S.E. slope.
40.20	Telephone line, bears N 65°E and S 65°W.
51.45	High ridge, bears S 60°W and N 60°E, 165 ft. above $\frac{1}{2}$ sec. cor. Desc. N.W. slope.
61.60	Draw, course N 50°W, 65 ft. below ridge. Asc. SW. slope.
67.10	Spur, slopes N 85°W, 45 ft. above draw. Desc. N.E. slope.
69.55	Draw, course N 70°W, 30 ft. below spur. Asc. S.W slope.
73.60	Spur, slopes S 75°W, 75 ft. above draw. Desc. N.E. slope.
75.35	Draw, course N 80°W, 10 ft. below spur. Asc. S.W. slope.
80.00	30 ft. above draw.
	Set an iron post, 3 ft. long, 3 ins. dia., 24 ins. in the ground for cor. of secs. 25, 30, 31 and 36, with