

Petracement and Resurvey of the  
First Standard Parallel North through Range 56 East.

chains

limestone, 4x6x8 ins. above ground, firmly set, marked and witnessed as described by the surveyor general; therefore the true course for this, the W. half mile is S.89° 45'E. and the distance, 40.46 chs.

From this standard  $\frac{1}{4}$  corner, just described, I retrace East on the S. bdy. of sec. 36 with continous chaining.

45.00 Dry wash, 10 lks. wide, 2 ft. deep, drains NW.

65.00 Dry wash, 20 lks. wide, 3 ft. deep, drains S.75°W.

80.90 Fall 23 lks. N. of the standard corner of Tps. 6 N., Rs. 56 and 57 E., which is a brown quartzite stone, 3x8x12 ins. above ground, firmly set in mound of earth and stone, marked and witnessed as described by the surveyor general; therefore the true course for this the E. half mile is S.89° 40'E., and the distance, 40.44 chs.

Land, rolling with a general drainage to the NW.; soil, coarse brown, black and white gravel and scattering loose quartzite rock on surface; subsoil, light brown gravelly loam of medium texture; no timber; medium undergrowth of shadscale, greasewood and scattering grass with scant grazing on the mile.

From the cor. of Tps. 5 and 6 N., Rs. 55 and 56 E., heretofore described, I resurvey

S.89° 45'E., on the First Standard Parallel North and S. bdy. of sec. 31.

Over very gently rolling land through medium undergrowth of shadscale and greasewood and scattering sage brush and grass.

40.20 Dry wash, 10 lks. wide,  $1\frac{1}{2}$  ft. deep, drains N.

40.49 By proportional measurement

Set an iron post, 3 ft. long, 1 inch in diameter, 26 ins. in the ground for standard  $\frac{1}{4}$  sec. cor., with brass cap marked

SC  
 $\frac{1}{4}$   
S31