

Retracement and Resurvey of the  
Ruby Valley Guide Meridian  
through Tps. 5 N., Rs. 55 and 56 East.

## Chains

Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor., with brass cap marked

$\frac{1}{4}$ S1  
|  
1916

Dig pits, 18x18x12 ins., N. and S. of post, 3 ft. dist.; and bury the old  $\frac{1}{4}$  cor. post alongside of iron post.

From this  $\frac{1}{4}$  sec. cor., just described and with continuous chaining, I resurvey

N.0° 16'E. between secs. 1 and 6.

80.42 Intersect the cor. of Tps. 5 and 6 N., Rs. 55 and 56 E., heretofore described.

Land, gently rolling with a general drainage to the NW.; soil, light brown sandy clay loam mixed with some white alkali, 36 ins. deep; no timber; medium undergrowth of shadscale and greasewood and scattering grass and sage brush; scant grazing on the mile.

-----

South Boundary of T.5 N., R.56 E.

From the cor. of Tps. 4 and 5 N., Rs. 55 and 56 E., heretofore described

East, bet. secs. 6 and 31.

Over rolling land, through scant undergrowth of shadscale and scattering grass.

Ascend gradually.

5.00 Dry wash, 15 lks. wide, 3 ft. deep, drains NW.

20.90 Wagon Road, bears N. and S.

35.00 Dry wash, 12 lks. wide,  $1\frac{1}{2}$  ft. deep, drains N.20°W.

37.20 Dry wash, 10 lks. wide, 3 ft. deep, drains NW.

37.70 Set an iron post, 3 ft. long, 1 in. in dia., 26 ins. in the ground for  $\frac{1}{4}$  sec. cor., with brass cap marked

S31  
-----  
S6

1916

and raise a mound of stone, 2 ft. base,  $1\frac{1}{2}$  ft. high, N.